

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | L G B 5 1 3 4 0              |
| 光源       | LED5000_70_1670 ×1 1670.0 lm |
| 管理番号     | K0154732 ( 0 ) DB 1          |
| BZ分類     | BZ6/0.7/BZ5                  |

| 器具効率     |         | 100 %           | 反射率     | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |   |   |  |   |
|----------|---------|-----------------|---------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|---|---|--|---|
|          |         |                 |         | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |   |   |  |   |
|          |         |                 |         | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |   |   |  |   |
| 上方光束     |         | 16 %            | 室指数     | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z | C |  | M |
| 下方光束     |         | 84 %            |         |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |   |   |  |   |
| 保守率      |         | 良<br>中<br>否     | 0.69    | 0.6           | 53   | 40 | 33 | 27 | 51   | 39 | 32 | 27 | 47   | 37 | 30 | 26 | 43   | 35 | 29 | 25 | 22  |  |   |   |  |   |
|          |         |                 | 0.67    | 0.8           | 62   | 50 | 42 | 37 | 60   | 49 | 41 | 36 | 55   | 46 | 39 | 34 | 51   | 43 | 38 | 33 | 30  |  |   |   |  |   |
|          |         |                 | 0.63    | 1.0           | 69   | 58 | 50 | 44 | 66   | 56 | 48 | 43 | 61   | 52 | 46 | 41 | 56   | 49 | 44 | 39 | 35  |  |   |   |  |   |
|          |         |                 |         | 1.25          | 75   | 64 | 57 | 51 | 72   | 62 | 55 | 50 | 66   | 59 | 52 | 48 | 61   | 55 | 50 | 46 | 41  |  |   |   |  |   |
| 下方投影面積   |         | cm <sup>2</sup> | 1.5     | 79            | 69   | 62 | 56 | 76 | 67   | 60 | 55 | 70 | 63   | 57 | 53 | 65 | 59   | 54 | 50 | 45 |     |  |   |   |  |   |
| 等価発光面積   |         | cm <sup>2</sup> | 2.0     | 84            | 76   | 70 | 64 | 81 | 74   | 68 | 63 | 75 | 69   | 64 | 60 | 70 | 65   | 61 | 57 | 52 |     |  |   |   |  |   |
| 取付<br>高さ | 器具間隔最大限 |                 | 2.5     | 88            | 81   | 75 | 70 | 85 | 78   | 73 | 68 | 79 | 74   | 69 | 65 | 74 | 69   | 66 | 62 | 57 |     |  |   |   |  |   |
|          | 横方向 (A) |                 | 縦方向 (B) | 3.0           | 90   | 84 | 79 | 74 | 87   | 82 | 77 | 73 | 81   | 77 | 73 | 69 | 76   | 72 | 69 | 66 | 60  |  |   |   |  |   |
| 1.5m     | 2.07 m  | 1.97 m          | 4.0     | 94            | 89   | 84 | 80 | 91 | 86   | 82 | 78 | 85 | 81   | 78 | 75 | 79 | 76   | 73 | 71 | 65 |     |  |   |   |  |   |
| 2        | 2.74    | 2.54            | 5.0     | 96            | 92   | 88 | 84 | 93 | 89   | 85 | 82 | 87 | 84   | 81 | 78 | 81 | 79   | 76 | 74 | 68 |     |  |   |   |  |   |
| 2.5      | 3.41    | 3.13            | 7.0     | 98            | 95   | 92 | 89 | 95 | 92   | 89 | 87 | 89 | 87   | 85 | 83 | 84 | 82   | 80 | 78 | 72 |     |  |   |   |  |   |
| 3        | 4.08    | 3.73            | 10.0    | 100           | 98   | 95 | 93 | 97 | 95   | 93 | 91 | 91 | 89   | 88 | 86 | 86 | 84   | 83 | 82 | 75 |     |  |   |   |  |   |

