

屋内照明器具特性	
品番 (品名)	LGB51856
光源	LED5000_70_538 ×1 538.0 lm
管理番号	K0154735 (0) DB 1
BZ分類	BZ6/0.7/BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 6 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		8 4 %																				
保守率		良 中 否	0 . 6 9	0 . 6	5 3	4 0	3 2	2 7	5 1	3 9	3 2	2 7	4 7	3 7	3 0	2 6	4 3	3 5	2 9	2 5	2 2	
			0 . 6 7	0 . 8	6 2	5 0	4 2	3 6	6 0	4 9	4 1	3 6	5 5	4 6	3 9	3 4	5 1	4 3	3 8	3 3	3 0	
			0 . 6 3	1 . 0	6 8	5 7	4 9	4 3	6 6	5 6	4 8	4 3	6 1	5 2	4 6	4 1	5 6	4 9	4 4	3 9	3 5	
				1 . 2 5	7 4	6 4	5 6	5 0	7 1	6 2	5 5	4 9	6 6	5 8	5 2	4 7	6 1	5 5	5 0	4 6	4 1	
下方投影面積		c m ²		1 . 5	7 8	6 9	6 2	5 6	7 5	6 7	6 0	5 5	7 0	6 3	5 7	5 2	6 5	5 9	5 4	5 0	4 6	
等価発光面積			c m ²	2 . 0	8 4	7 6	7 0	6 4	8 1	7 4	6 8	6 3	7 5	6 9	6 4	6 0	7 0	6 5	6 1	5 7	5 2	
取付高さ	器具間隔最大限		2 . 5	8 8	8 1	7 5	7 0	8 5	7 8	7 3	6 8	7 9	7 4	6 9	6 5	7 3	6 9	6 6	6 2	5 7		
	横方向 (A)	縦方向 (B)	3 . 0	9 0	8 4	7 9	7 4	8 7	8 1	7 7	7 2	8 1	7 7	7 3	6 9	7 6	7 2	6 9	6 6	6 0		
H m	1 . 3 5 H m	1 . 2 3 H m	4 . 0	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 8	8 5	8 1	7 8	7 4	7 9	7 6	7 3	7 1	6 5		
			5 . 0	9 5	9 1	8 7	8 4	9 2	8 9	8 5	8 2	8 7	8 4	8 1	7 8	8 1	7 9	7 6	7 4	6 8		
			7 . 0	9 8	9 5	9 2	8 9	9 5	9 2	8 9	8 7	8 9	8 7	8 4	8 2	8 4	8 2	8 0	7 8	7 2		
			1 0 . 0	1 0 0	9 7	9 5	9 3	9 7	9 4	9 2	9 1	9 1	8 9	8 8	8 6	8 6	8 4	8 3	8 2	7 5		

