

屋内照明器具特性	
品番 (品名)	L G B 5 1 8 5 7
光源	LED3500_70_495 ×1 495.0 l m
管理番号	K0154735 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 9	0 . 6	5 3	4 0	3 2	2 7	5 1	3 9	3 2	2 7	4 7	3 7	3 0	2 6	4 3	3 5	2 9	2 5	2 2				
			0 . 6 7	0 . 8	6 2	5 0	4 2	3 6	6 0	4 9	4 1	3 6	5 5	4 6	3 9	3 4	5 1	4 3	3 8	3 3	3 0				
			0 . 6 3	1 . 0	6 8	5 7	4 9	4 3	6 6	5 6	4 8	4 3	6 1	5 2	4 6	4 1	5 6	4 9	4 4	3 9	3 5				
				1 . 2 5	7 4	6 4	5 6	5 0	7 1	6 2	5 5	4 9	6 6	5 8	5 2	4 7	6 1	5 5	5 0	4 6	4 1				
下方投影面積		c m ²		1 . 5	7 8	6 9	6 2	5 6	7 5	6 7	6 0	5 5	7 0	6 3	5 7	5 2	6 5	5 9	5 4	5 0	4 6				
			等価発光面積		c m ²	2 . 0	8 4	7 6	7 0	6 4	8 1	7 4	6 8	6 3	7 5	6 9	6 4	6 0	7 0	6 5	6 1	5 7	5 2		
取付 高さ	器具間隔最大限		2 . 5	8 8	8 1	7 5	7 0	8 5	7 8	7 3	6 8	7 9	7 4	6 9	6 5	7 3	6 9	6 6	6 2	5 7					
	横方向 (A) 縦方向 (B)		3 . 0	9 0	8 4	7 9	7 4	8 7	8 1	7 7	7 2	8 1	7 7	7 3	6 9	7 6	7 2	6 9	6 6	6 0					
H m	1 . 3 5 H m	1 . 2 3 H m	4 . 0	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 8	8 5	8 1	7 8	7 4	7 9	7 6	7 3	7 1	6 5					
			5 . 0	9 5	9 1	8 7	8 4	9 2	8 9	8 5	8 2	8 7	8 4	8 1	7 8	8 1	7 9	7 6	7 4	6 8					
			7 . 0	9 8	9 5	9 2	8 9	9 5	9 2	8 9	8 7	8 9	8 7	8 4	8 2	8 4	8 2	8 0	7 8	7 2					
			1 0 . 0	1 0 0	9 7	9 5	9 3	9 7	9 4	9 2	9 1	9 1	8 9	8 8	8 6	8 6	8 4	8 3	8 2	7 5					

