

屋内照明器具特性	
品番 (品名)	L G B 5 1 8 8 6
光源	LED5000_70_2250 ×1 2250.0 lm
管理番号	K0154730 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.69	0.6	52	40	32	27	50	39	31	26	46	36	30	25	43	34	28	24	21
			0.67	0.8	62	50	42	36	59	48	41	35	55	45	39	34	50	43	37	32	29
			0.63	1.0	68	57	49	43	65	55	48	42	60	52	45	40	56	48	43	39	34
				1.25	74	64	56	50	71	62	55	49	66	58	52	47	61	54	49	45	40
下方投影面積		cm ²		1.5	78	69	61	56	75	67	60	54	69	62	57	52	64	58	53	49	44
			等価発光面積		cm ²	2.0	84	76	69	64	81	73	67	62	75	69	64	59	69	64	60
取付高さ	器具間隔最大限		2.5	87	80	75	69	84	78	72	68	78	73	68	64	73	68	65	61	55	
	横方向 (A)	縦方向 (B)	3.0	90	84	78	74	87	81	76	72	81	76	72	68	75	71	68	65	59	
1.5m	2.08 m	2.09 m	4.0	93	88	84	80	90	85	81	78	84	80	77	74	78	75	72	70	63	
2	2.75	2.64	5.0	95	91	87	84	92	88	85	82	86	83	80	77	80	78	75	73	66	
2.5	3.42	3.22	7.0	98	94	91	89	95	92	89	86	88	86	84	82	83	81	79	77	70	
3	4.08	3.81	10.0	100	97	95	93	96	94	92	90	90	89	87	85	85	83	82	81	73	

