

屋内照明器具特性	
品番 (品名)	LGB52622
光源	LED5000_70_1700 ×1 1700.0 lm
管理番号	K0147582 (0) DB 1
BZ分類	BZ6/0.7/BZ5/2.8/BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		9 % 91 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	53	41	33	27	51	40	32	27	48	38	31	26	45	36	30	25	23	
			0.6	0.8	63	51	42	36	61	49	42	36	57	47	40	35	53	45	39	34	31	
			0.56	1.0	69	58	49	43	67	56	49	43	63	54	47	42	59	51	45	40	37	
			1.25	1.25	75	64	56	50	72	63	55	50	68	60	53	48	64	57	51	47	43	
下方投影面積 等価発光面積		cm ² cm ²	1.5	79	69	62	56	77	68	60	55	72	64	58	53	68	61	56	52	48		
			2.0	85	76	69	64	82	74	68	63	77	71	65	61	73	67	63	59	55		
取付 高さ	器具間隔最大限		2.5	88	81	75	69	86	79	73	68	81	75	70	66	76	72	68	64	60		
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	88	82	77	73	83	78	74	70	79	75	71	68	63		
H _m	1.30H _m	1.30H _m	4.0	94	89	84	80	92	87	82	79	87	83	79	76	82	79	76	73	68		
			5.0	96	92	88	84	94	90	86	82	89	86	82	80	85	82	79	77	72		
			7.0	99	95	92	89	96	93	90	87	92	89	87	84	87	85	83	81	76		
			10.0	101	98	96	93	98	96	94	92	94	92	90	88	90	88	86	85	80		

