

屋内照明器具特性	
品番 (品名)	LGB53015
光源	LED5000_70_1985 ×1 1985.0 lm
管理番号	K0141003 (0) DB1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束		10 %		床	10 %				10 %				10 %				10 %				0 %	
下方光束		90 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	54	42	34	29	52	41	34	28	49	39	32	28	46	37	31	27	24	
			0.6	0.8	64	52	44	38	62	51	43	38	58	48	42	37	54	46	40	36	33	
			0.56	1.0	70	59	51	45	68	58	50	45	64	55	49	44	60	52	47	42	39	
				1.25	76	66	58	53	74	64	57	52	69	61	55	50	65	58	53	49	45	
下方投影面積		cm ²	1.5	80	71	64	58	78	69	63	57	73	66	60	55	69	63	58	54	50		
等価発光面積		cm ²	2.0	86	78	72	66	83	76	70	65	78	72	67	63	74	69	65	61	57		
取付 高さ	器具間隔最大限		2.5	89	83	77	72	87	81	75	71	82	77	72	68	77	73	69	66	61		
	横方向 (A) 縦方向 (B)		3.0	92	86	81	76	89	84	79	75	84	80	76	72	80	76	73	70	65		
1.5m	1.89 m	1.87 m	4.0	95	90	86	82	93	88	84	81	88	84	81	78	83	80	77	75	70		
2	2.5	2.48	5.0	97	93	89	86	95	91	88	84	90	87	84	81	85	83	80	78	73		
2.5	3.13	3.1	7.0	99	96	94	91	97	94	92	89	92	90	88	86	88	86	84	82	77		
3	3.75	3.72	10.0	101	99	97	95	99	97	95	93	94	92	91	89	90	88	87	86	80		

