

屋内照明器具特性	
品番 (品名)	LGB81504 (CEILING)
光源	LGB81504 ×1 208.0 lm
管理番号	K0116941 (0) DD1
BZ分類	BZ6/0.7/BZ5/1.8/BZ6

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	52	40	32	26	50	38	31	26	45	36	29	24	41	33	27	23	20	
			0.6	0.8	61	49	41	35	58	48	40	34	53	44	38	33	49	41	36	31	27	
				1.0	67	56	48	42	64	54	47	41	59	50	44	39	54	47	41	37	33	
			0.56	1.25	73	63	55	49	70	61	53	48	64	56	50	45	59	52	47	43	38	
下方投影面積		cm ²		1.5	77	68	60	54	74	65	58	53	68	61	55	50	62	56	51	47	42	
			等価発光面積	cm ²	2.0	83	74	68	62	79	72	66	61	73	67	62	57	67	62	58	54	48
取付 高さ	器具間隔最大限			2.5	86	79	73	68	83	76	71	66	76	71	66	62	71	66	62	59	53	
	横方向 (A)		縦方向 (B)	3.0	89	82	77	72	85	80	75	70	79	74	70	66	73	69	66	63	56	
H m	1.28 H m		1.28 H m	4.0	92	87	82	78	89	84	80	76	82	78	75	72	76	73	70	67	61	
				5.0	94	90	86	82	91	87	83	80	84	81	78	75	78	76	73	71	64	
				7.0	97	93	90	87	93	90	87	85	87	84	82	80	81	79	77	75	67	
				10.0	99	96	94	91	95	93	91	89	89	87	85	83	83	81	80	78	71	

