

屋内照明器具特性	
品番 (品名)	L G B 8 1 5 1 1
光源	L G B 8 1 5 1 1 × 1 2 8 2 . 0 l m
管理番号	K 0 1 1 8 1 2 2 (0) D R 1
B Z 分類	B Z 3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 8	4 7	4 1	3 6	5 5	4 6	4 0	3 5	4 9	4 2	3 7	3 3	4 5	3 9	3 4	3 1	2 8
			0 . 6	0 . 8	6 7	5 7	5 0	4 6	6 3	5 5	4 9	4 4	5 7	5 0	4 5	4 2	5 1	4 6	4 2	3 9	3 4
			0 . 5 6	1 . 0	7 2	6 4	5 7	5 3	6 9	6 1	5 5	5 1	6 2	5 6	5 1	4 8	5 6	5 1	4 7	4 4	3 9
				1 . 2 5	7 8	7 0	6 4	5 9	7 4	6 7	6 1	5 7	6 6	6 1	5 7	5 3	5 9	5 5	5 2	4 9	4 3
下方投影面積		c m ²	1 . 5	8 1	7 4	6 8	6 4	7 7	7 1	6 6	6 2	6 9	6 4	6 0	5 7	6 2	5 8	5 5	5 3	4 6	
			等価発光面積	c m ²	2 . 0	8 6	8 0	7 5	7 1	8 1	7 6	7 2	6 8	7 3	6 9	6 6	6 3	6 6	6 3	6 0	5 8
取付 高さ	器具間隔最大限		2 . 5	8 9	8 3	7 9	7 6	8 4	8 0	7 6	7 3	7 6	7 2	6 9	6 7	6 8	6 5	6 3	6 1	5 2	
	横方向 (A) 縦方向 (B)		3 . 0	9 1	8 6	8 2	7 9	8 6	8 2	7 9	7 6	7 7	7 4	7 2	7 0	6 9	6 7	6 5	6 4	5 4	
H m	1 . 0 0 H m	1 . 1 0 H m	4 . 0	9 3	9 0	8 6	8 4	8 8	8 5	8 3	8 0	8 0	7 7	7 5	7 3	7 1	7 0	6 8	6 7	5 7	
			5 . 0	9 5	9 2	8 9	8 7	9 0	8 7	8 5	8 3	8 1	7 9	7 7	7 6	7 3	7 1	7 0	6 9	5 8	
			7 . 0	9 6	9 4	9 2	9 0	9 2	9 0	8 8	8 6	8 3	8 1	8 0	7 9	7 4	7 3	7 2	7 1	6 0	
			1 0 . 0	9 8	9 6	9 5	9 3	9 3	9 2	9 0	8 9	8 4	8 3	8 2	8 1	7 5	7 5	7 4	7 3	6 2	

