

屋内照明器具特性	
品番 (品名)	L G B 8 1 5 6 4 Z
光源	L D A 4 L - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 l m
管理番号	K 0 1 3 4 3 1 8 (0) D B 1
B Z 分類	B Z 8 / 1 . 4 / B Z 7 / 1 . 8 / B Z 8 / 2 . 8 / B Z 7 / 8 . 5 / B Z 8

器具効率		5 7 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		2 2 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		3 5 %																							
保守率		良 中 否	0 . 6 3	0 . 6	2 6	1 9	1 4	1 1	2 4	1 8	1 3	1 0	2 1	1 5	1 2	9	1 7	1 3	1 0	8	5				
			0 . 6	0 . 8	3 1	2 4	1 9	1 5	2 9	2 2	1 8	1 5	2 4	1 9	1 6	1 3	2 1	1 6	1 3	1 1	8				
				1 . 0	3 4	2 7	2 2	1 9	3 2	2 6	2 1	1 8	2 7	2 2	1 8	1 6	2 3	1 9	1 6	1 4	1 0				
			0 . 5 6	1 . 2 5	3 7	3 1	2 6	2 2	3 5	2 9	2 5	2 1	3 0	2 5	2 1	1 9	2 5	2 1	1 9	1 6	1 2				
下方投影面積		c m ²	1 . 5	4 0	3 4	2 9	2 5	3 7	3 1	2 7	2 4	3 2	2 7	2 4	2 1	2 7	2 3	2 1	1 8	1 3					
			等価発光面積	c m ²	2 . 0	4 3	3 8	3 3	3 0	4 0	3 5	3 1	2 8	3 4	3 1	2 7	2 5	2 9	2 6	2 4	2 2	1 6			
取付 高さ	器具間隔最大限		2 . 5	4 5	4 0	3 6	3 3	4 2	3 8	3 4	3 1	3 6	3 3	3 0	2 8	3 1	2 8	2 6	2 4	1 8					
	横方向 (A) 縦方向 (B)		3 . 0	4 6	4 2	3 9	3 6	4 3	4 0	3 6	3 4	3 8	3 5	3 2	3 0	3 2	3 0	2 8	2 6	2 0					
H m	1 . 5 0 H m	1 . 5 0 H m	4 . 0	4 8	4 5	4 2	3 9	4 5	4 2	4 0	3 7	4 0	3 7	3 5	3 3	3 4	3 2	3 0	2 9	2 2					
			5 . 0	5 0	4 7	4 4	4 2	4 7	4 4	4 2	3 9	4 1	3 9	3 7	3 5	3 5	3 3	3 2	3 0	2 4					
			7 . 0	5 1	4 9	4 7	4 5	4 8	4 6	4 4	4 2	4 2	4 1	3 9	3 8	3 7	3 5	3 4	3 3	2 6					
			1 0 . 0	5 3	5 1	4 9	4 8	5 0	4 8	4 6	4 5	4 4	4 2	4 1	4 0	3 8	3 7	3 6	3 5	2 8					

