

屋内照明器具特性	
品番 (品名)	L G B 8 1 6 1 3
光源	LDA4 WW- H- E 1 7 / E / S / W/ 2 × 1 4 4 0 . 0 l m
管理番号	K 0 1 6 4 1 3 6 (1) D 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		53 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束		2 %	室指数	照明率 (X0.01) ZCM																	
下方光束		51 %																			
保守率		良 中 否	0.67	0.6	32	26	22	19	31	26	22	19	30	25	22	19	28	24	21	19	18
			0.63	0.8	38	32	29	26	37	32	28	26	35	31	28	25	34	30	27	25	24
			0.56	1.0	41	36	33	30	40	36	33	30	39	35	32	30	37	34	31	29	28
				1.25	44	40	37	34	43	39	36	34	42	38	36	34	40	37	35	33	32
下方投影面積		cm ²	1.5	46	42	39	37	45	42	39	37	44	41	38	36	42	39	37	36	34	
等価発光面積		cm ²	2.0	49	46	43	41	48	45	43	41	46	44	42	40	45	43	41	39	38	
取付 高さ	器具間隔最大限		2.5	50	48	46	44	50	47	45	43	48	46	44	43	46	44	43	42	40	
	横方向 (A) 縦方向 (B)		3.0	52	49	47	46	51	49	47	45	49	47	46	44	47	46	45	43	42	
H m	1.38 H m	1.38 H m	4.0	53	51	50	48	52	50	49	48	50	49	48	47	49	47	46	46	44	
			5.0	54	52	51	50	53	51	50	49	51	50	49	48	49	48	48	47	45	
			7.0	55	53	52	52	54	53	52	51	52	51	50	50	50	50	49	48	46	
			10.0	55	54	54	53	54	54	53	52	53	52	52	51	51	51	50	50	48	

