

屋内照明器具特性	
品番 (品名)	L G B 8 1 7 6 1
光源	LED2700_70_2970 ×1 2970.0 lm
管理番号	K0142374 (0) DR 1
B Z 分類	B Z 6

器具効率		100 % 上方光束 50 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	48	36	29	23	44	34	27	22	37	29	23	19	30	24	20	16	11
			0.6	0.8	56	45	37	32	52	42	35	30	43	36	30	26	36	30	25	22	16
			0.56	1.0	62	52	44	38	57	48	41	36	48	41	35	31	40	34	30	26	19
				1.25	68	58	50	45	62	54	47	42	52	46	41	36	43	38	34	31	22
下方投影面積		cm ²	1.5	72	63	55	50	66	58	52	47	56	49	44	40	46	41	37	34	24	
等価発光面積			cm ²	2.0	77	69	63	57	71	64	59	54	60	55	50	46	50	46	42	39	28
				2.5	81	74	68	63	74	68	63	59	63	58	54	51	52	49	46	43	31
取付 高さ	器具間隔最大限			3.0	83	77	72	67	77	71	67	63	65	61	57	54	54	51	48	46	33
	横方向 (A)		縦方向 (B)																		
1.5m	1.25 m	2.18 m		4.0	86	81	77	73	80	75	71	68	68	64	61	59	56	54	52	49	36
2	1.67	2.77		5.0	88	84	80	77	82	78	75	71	69	67	64	62	58	56	54	52	38
2.5	2.08	3.38		7.0	90	87	84	81	84	81	78	76	72	69	67	65	60	58	57	55	40
3	2.5	4		10.0	92	90	88	85	86	84	82	80	73	72	70	69	62	60	59	58	42

