

屋内照明器具特性	
品番 (品名)	L G B 8 1 7 6 3
光源	LED2700_70_1530 ×1 1530.0 lm
管理番号	K0142373 (0) DR 1
B Z 分類	B Z 5

器具効率		100 % 上方光束 50 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	0.6	50	39	32	27	46	36	30	25	39	31	26	22	33	27	23	19	14
			0.6	0.8	59	48	40	35	54	45	38	33	46	39	33	29	38	33	29	26	19	
			0.56	1.0	65	54	47	42	60	51	44	39	50	44	39	35	42	37	33	30	22	
				1.25	70	61	54	48	65	57	50	46	55	49	44	40	46	41	37	34	26	
下方投影面積		cm ²	1.5	74	65	59	53	68	61	55	50	58	52	48	44	48	44	41	38	28		
等価発光面積			2.0	79	72	66	61	73	67	62	57	62	57	53	50	52	48	45	43	32		
取付高さ	器具間隔最大限		2.5	82	76	71	66	76	71	66	62	65	61	57	54	54	51	49	46	34		
	横方向 (A) 縦方向 (B)		3.0	85	79	74	70	78	74	70	66	67	63	60	57	56	53	51	49	36		
1.5m	1.48 m	2.12 m	4.0	88	83	79	76	81	78	74	71	69	67	64	62	58	56	54	53	39		
2	1.89	2.69	5.0	89	86	82	79	83	80	77	74	71	69	66	64	60	58	56	55	41		
2.5	2.32	3.27	7.0	92	89	86	84	85	83	81	78	73	71	69	68	61	60	59	58	43		
3	2.39	3.88	10.0	93	91	89	87	87	85	83	82	75	73	72	71	63	62	61	60	45		

