

屋内照明器具特性	
品番 (品名)	L G B 8 1 8 7 6
光源	LED3500_70_916 ×1 916.0 l m
管理番号	K0153987 (0) DB 1
B Z 分類	BZ8 / 0.7 / BZ7

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		32 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		68 %																						
保守率		良 中 否	0.67	0.6	47	34	26	20	44	32	25	19	38	29	22	17	33	25	20	16	11			
			0.63	0.8	56	43	34	28	52	41	33	27	45	36	29	24	39	32	26	22	17			
			0.56	1.0	62	50	41	34	58	47	39	33	50	41	35	30	44	36	31	26	20			
				1.25	67	56	47	41	63	53	45	39	55	47	40	35	48	41	36	31	25			
下方投影面積		cm ²	1.5	71	61	53	46	67	57	50	44	59	51	45	40	51	45	40	35	28				
等価発光面積		cm ²	2.0	77	68	60	54	73	64	57	51	64	57	51	46	56	50	46	42	33				
取付 高さ	器具間隔最大限		2.5	81	73	66	60	76	69	62	57	67	61	56	51	59	54	50	46	37				
	横方向 (A)	縦方向 (B)	3.0	84	76	70	64	79	72	66	61	70	64	60	55	61	57	53	50	40				
1.5m	2.02 m	1.93 m	4.0	87	81	76	71	82	77	72	67	73	69	65	61	64	61	58	55	44				
2	2.69	2.54	5.0	89	84	79	75	85	80	75	72	75	72	68	65	67	64	61	58	48				
2.5	3.36	3.16	7.0	92	88	84	81	87	84	80	77	78	75	72	70	69	67	65	62	52				
3	4.01	3.78	10.0	95	91	88	86	90	87	84	82	81	78	76	74	72	70	68	66	55				

