

屋内照明器具特性	
品番 (品名)	LGB87001Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 lm
管理番号	K0122398 (1) DB1
BZ分類	BZ4/0.7/BZ3/0.9/BZ4

器具効率		34 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		4 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		30 %																						
保守率		良 中 否	0.63	0.6	20	16	14	12	19	16	14	12	18	15	13	12	17	14	13	11	11			
			0.6	0.8	23	20	17	15	22	19	17	15	21	18	16	15	20	17	16	14	13			
				1.0	25	22	20	18	24	21	19	18	23	20	19	17	22	19	18	17	15			
			0.56	1.25	27	24	22	20	26	23	21	20	25	22	21	19	23	21	20	19	17			
下方投影面積		cm ²	1.5	28	26	24	22	27	25	23	22	26	24	22	21	24	23	21	20	19				
等価発光面積		cm ²	2.0	30	28	26	24	29	27	25	24	27	26	24	23	26	25	23	22	21				
取付 高さ	器具間隔最大限		2.5	31	29	28	26	30	28	27	26	28	27	26	25	27	26	25	24	22				
	横方向 (A) 縦方向 (B)		3.0	32	30	29	27	31	29	28	27	29	28	27	26	28	27	26	25	23				
H m	0.74 H m	1.24 H m	4.0	33	31	30	29	32	31	30	29	30	29	28	28	29	28	27	26	25				
			5.0	33	32	31	30	32	31	31	30	31	30	29	29	29	28	28	27	25				
			7.0	34	33	32	32	33	32	32	31	31	31	30	30	30	29	29	28	26				
			10.0	34	34	33	33	33	33	32	32	32	31	31	31	30	30	30	29	27				

