

屋内照明器具特性	
品番 (品名)	L G B 8 7 0 1 2 Z
光源	LDA4 L - H - E17 / E / S / W/ 2 ×1 440.0 l m
管理番号	K0122401 (2) DB 1
B Z 分類	BZ4 / 0.9 / BZ3

器具効率		60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z C M															
保守率		良 中 否	0.67	0.6	34	27	23	20	33	26	22	19	30	25	21	19	28	23	20	18	16	
			0.63	0.8	40	34	30	27	39	33	29	26	36	31	28	25	33	29	26	24	22	
			0.56	1.0	44	39	34	31	43	37	34	31	39	35	32	29	37	33	30	28	26	
				1.25	48	43	39	36	46	41	38	35	43	39	36	34	39	36	34	32	29	
下方投影面積		c m ²	1.5	50	45	42	39	48	44	41	38	45	41	39	36	41	39	37	35	32		
等価発光面積				c m ²	2.0	53	49	46	44	51	48	45	43	47	45	42	41	44	42	40	39	35
取付 高さ	器具間隔最大限				2.5	55	52	49	47	53	50	48	46	49	47	45	43	46	44	42	41	37
	横方向 (A)		縦方向 (B)		3.0	56	53	51	49	54	52	50	48	50	49	47	45	47	45	44	43	39
H m	1.32 H m		1.49 H m		4.0	58	56	54	52	56	54	52	51	52	50	49	48	48	47	46	45	41
				5.0	59	57	55	54	57	55	54	52	53	52	51	49	49	48	47	47	42	
				7.0	60	59	57	56	58	57	56	55	54	53	52	51	50	50	49	48	44	
				10.0	61	60	59	58	59	58	57	56	55	54	54	53	51	51	50	50	45	

