

屋内照明器具特性	
品番 (品名)	L G B 8 7 0 2 0 Z
光源	LDA4 L - H - E17 / E / S / W/ 2 × 1 440.0 l m
管理番号	K0123210 (1) DB 1
BZ分類	BZ9 / 0.7 / BZ8

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	31	23	17	14	28	21	16	12	23	17	13	10	18	13	10	8	4
			0.63	0.8	37	29	23	19	34	26	21	17	27	21	17	14	21	17	14	11	6
			0.56	1.0	41	33	27	23	37	30	25	21	30	25	21	17	23	19	16	14	8
				1.25	45	37	32	27	41	34	29	25	33	28	24	21	26	22	19	16	9
下方投影面積		cm ²		1.5	48	41	35	31	43	37	32	28	35	30	27	24	27	24	21	19	11
			等価発光面積	cm ²	2.0	52	46	41	36	47	42	37	33	38	34	31	28	30	27	24	22
取付 高さ	器具間隔最大限		2.5	54	49	44	40	49	45	41	37	40	37	34	31	32	29	27	25	15	
	横方向 (A) 縦方向 (B)		3.0	56	51	47	43	51	47	43	40	42	39	36	33	33	31	29	27	17	
H m	1.57 H m	1.29 H m	4.0	58	54	51	48	53	50	47	44	44	41	39	37	35	33	31	29	19	
			5.0	60	57	53	51	55	52	49	47	45	43	41	39	36	35	33	31	20	
			7.0	62	59	57	54	57	54	52	50	47	45	43	42	38	36	35	34	22	
			10.0	63	61	59	57	58	56	55	53	48	47	46	44	39	38	37	36	24	

