

屋内照明器具特性	
品番 (品名)	L G B 8 7 0 3 0 Z
光源	L D A 4 L - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 l m
管理番号	K 0 1 7 1 4 3 0 (0) D B 1
B Z 分類	B Z 8 / 4 . 5 / B Z 7

器具効率		7 3 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		3 7 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		3 6 %																				
保守率		良	0 . 6 3	0 . 6	3 3	2 4	1 8	1 4	3 0	2 2	1 7	1 3	2 5	1 8	1 4	1 1	2 0	1 5	1 1	9	5	
		中	0 . 6	0 . 8	3 9	3 0	2 4	2 0	3 6	2 8	2 2	1 8	2 9	2 3	1 9	1 6	2 4	1 9	1 5	1 3	8	
		否	0 . 5 6	1 . 0	4 3	3 5	2 9	2 4	4 0	3 2	2 7	2 2	3 3	2 7	2 2	1 9	2 6	2 2	1 8	1 6	1 0	
				1 . 2 5	4 7	3 9	3 4	2 9	4 3	3 6	3 1	2 7	3 6	3 0	2 6	2 3	2 9	2 5	2 2	1 9	1 2	
下方投影面積		c m ²		1 . 5	5 0	4 3	3 7	3 3	4 6	4 0	3 4	3 0	3 8	3 3	2 9	2 6	3 1	2 7	2 4	2 1	1 4	
等価発光面積		c m ²		2 . 0	5 4	4 8	4 3	3 8	5 0	4 4	4 0	3 6	4 2	3 7	3 4	3 0	3 4	3 1	2 8	2 5	1 7	
取付高さ	器具間隔最大限			2 . 5	5 7	5 1	4 7	4 3	5 2	4 7	4 3	4 0	4 4	4 0	3 7	3 4	3 6	3 3	3 0	2 8	1 9	
	横方向 (A)		縦方向 (B)	3 . 0	5 9	5 4	5 0	4 6	5 4	5 0	4 6	4 3	4 6	4 2	3 9	3 6	3 7	3 5	3 2	3 0	2 1	
H m	1 . 6 0 H m	1 . 8 1 H m	4 . 0	6 1	5 7	5 4	5 0	5 7	5 3	5 0	4 7	4 8	4 5	4 2	4 0	3 9	3 7	3 5	3 3	2 3		
			5 . 0	6 3	5 9	5 6	5 3	5 8	5 5	5 2	5 0	4 9	4 7	4 5	4 2	4 1	3 9	3 7	3 5	2 5		
			7 . 0	6 5	6 2	6 0	5 7	6 0	5 8	5 5	5 3	5 1	4 9	4 7	4 6	4 2	4 1	4 0	3 8	2 7		
			1 0 . 0	6 6	6 4	6 2	6 0	6 2	6 0	5 8	5 6	5 3	5 1	5 0	4 8	4 4	4 3	4 2	4 1	2 9		

