

屋内照明器具特性	
品番 (品名)	L G B 8 7 0 4 6 Z
光源	LDA4 L - H - E17 / E / S / W/ 2 ×1 440.0 l m
管理番号	K0122399 (2) DB 1
B Z 分類	B Z 4

器具効率		48 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	27	22	18	16	26	21	18	16	24	20	17	15	22	19	16	15	13
			0.6	0.8	31	26	23	21	30	26	22	20	28	24	21	19	26	23	20	19	17
			0.56	1.0	34	30	26	24	33	29	26	23	31	27	25	22	28	26	23	22	20
			1.25	37	33	30	27	36	32	29	27	33	30	27	26	31	28	26	24	22	
下方投影面積		c m ²	1.5	39	35	32	30	37	34	31	29	35	32	30	28	32	30	28	26	24	
			等価発光面積		c m ²	2.0	41	38	36	33	40	37	35	33	37	35	33	31	34	33	31
取付高さ	器具間隔最大限					2.5	43	40	38	36	41	39	37	35	39	37	35	33	36	34	33
		横方向 (A)	縦方向 (B)	3.0	44	42	40	38	42	40	38	37	40	38	36	35	37	35	34	33	30
H m	0.86 H m	1.29 H m	4.0	45	43	42	40	44	42	41	39	41	40	38	37	38	37	36	35	32	
			5.0	46	45	43	42	45	43	42	41	42	41	40	39	39	38	37	36	33	
			7.0	47	46	45	44	46	45	44	43	43	42	41	40	40	39	39	38	35	
			10.0	48	47	46	45	46	46	45	44	43	43	42	42	41	40	40	39	36	

