

屋内照明器具特性	
品番 (品名)	L G B 8 7 0 8 2 K
光源	LDA3 L - H - E17 / 25 E / W ×1 360.0 l m
管理番号	K0123530 (0) DB 1
B Z 分類	BZ4 / 0.9 / BZ5 / 6.0 / BZ6

器具効率		8 3 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	4 6	3 6	3 0	2 6	4 4	3 5	2 9	2 6	4 0	3 2	2 8	2 4	3 6	3 0	2 6	2 3	2 0
			0 . 6 3	0 . 8	5 3	4 4	3 7	3 3	5 0	4 2	3 6	3 2	4 5	3 9	3 4	3 0	4 1	3 6	3 1	2 8	2 5
			0 . 5 6	1 . 0	5 7	4 9	4 3	3 8	5 4	4 7	4 1	3 7	4 9	4 3	3 8	3 5	4 4	3 9	3 5	3 2	2 8
				1 . 2 5	6 2	5 4	4 8	4 3	5 9	5 1	4 6	4 2	5 3	4 7	4 3	3 9	4 8	4 3	3 9	3 6	3 2
下方投影面積		c m ²	1 . 5	6 5	5 7	5 2	4 7	6 1	5 5	5 0	4 5	5 6	5 0	4 6	4 2	5 0	4 6	4 2	3 9	3 4	
			2 . 0	6 9	6 2	5 7	5 3	6 5	6 0	5 5	5 1	5 9	5 5	5 1	4 8	5 4	5 0	4 7	4 4	3 8	
取付 高さ	器具間隔最大限		2 . 5	7 1	6 6	6 1	5 7	6 8	6 3	5 9	5 5	6 2	5 8	5 4	5 1	5 6	5 3	5 0	4 7	4 1	
	横方向 (A)	縦方向 (B)	3 . 0	7 3	6 8	6 4	6 0	7 0	6 6	6 2	5 8	6 4	6 0	5 7	5 4	5 8	5 5	5 2	5 0	4 3	
H m	1 . 0 9 H m	1 . 1 0 H m	4 . 0	7 6	7 2	6 8	6 5	7 2	6 9	6 6	6 3	6 6	6 3	6 0	5 8	6 0	5 7	5 5	5 3	4 6	
			5 . 0	7 7	7 4	7 1	6 8	7 4	7 1	6 8	6 5	6 7	6 5	6 3	6 1	6 1	5 9	5 7	5 6	4 8	
			7 . 0	7 9	7 7	7 4	7 2	7 6	7 3	7 1	6 9	6 9	6 7	6 6	6 4	6 3	6 2	6 0	5 9	5 1	
			1 0 . 0	8 1	7 9	7 7	7 5	7 7	7 6	7 4	7 2	7 1	6 9	6 8	6 7	6 5	6 3	6 2	6 1	5 3	

