

屋内照明器具特性	
品番 (品名)	L G B C 5 5 0 0 3
光源	LED5000_70_415 ×1 415.0 l m
管理番号	K0172990 (0) DR 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		9 9 %																					
保守率		良 中 否	0 . 6 7	0 . 6	5 7	4 5	3 8	3 2	5 6	4 5	3 7	3 2	5 4	4 4	3 7	3 2	5 1	4 2	3 6	3 2	3 0		
			0 . 6 3	0 . 8	6 7	5 6	4 8	4 3	6 6	5 5	4 8	4 2	6 3	5 4	4 7	4 2	6 0	5 2	4 6	4 2	4 0		
			0 . 5 6	1 . 0	7 4	6 3	5 6	5 0	7 2	6 2	5 5	5 0	6 9	6 1	5 4	4 9	6 6	5 9	5 3	4 9	4 7		
				1 . 2 5	8 0	7 0	6 3	5 7	7 8	6 9	6 2	5 7	7 5	6 7	6 1	5 6	7 2	6 5	6 0	5 6	5 3		
下方投影面積		cm ²	1 . 5	8 4	7 5	6 8	6 3	8 2	7 4	6 8	6 2	7 9	7 2	6 6	6 2	7 6	7 0	6 5	6 1	5 9			
等価発光面積		cm ²	2 . 0	8 9	8 2	7 6	7 1	8 8	8 1	7 5	7 1	8 4	7 9	7 4	7 0	8 1	7 6	7 2	6 9	6 6			
取付高さ	器具間隔最大限		2 . 5	9 3	8 6	8 1	7 7	9 1	8 5	8 0	7 6	8 8	8 3	7 9	7 5	8 5	8 1	7 7	7 4	7 1			
	横方向 (A) 縦方向 (B)		3 . 0	9 5	9 0	8 5	8 1	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 9	8 7	8 4	8 0	7 8	7 5			
H m	1 . 2 2 H m	1 . 2 2 H m	4 . 0	9 8	9 4	9 0	8 6	9 7	9 2	8 9	8 6	9 3	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 0			
			5 . 0	1 0 0	9 6	9 3	9 0	9 8	9 5	9 2	8 9	9 5	9 3	9 0	8 8	9 3	9 0	8 8	8 6	8 3			
			7 . 0	1 0 2	9 9	9 7	9 4	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 2	9 5	9 3	9 1	9 0	8 7			
			1 0 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 1	9 9	9 7	1 0 0	9 8	9 6	9 5	9 7	9 6	9 4	9 3	9 0			

