

屋内照明器具特性	
品番 (品名)	L G B C 8 1 0 2 2
光源	LED5000_70_1720 ×1 1720.0 lm
管理番号	K0147578 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5 / 2.8 / BZ6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
				室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 3	0 . 6	0 . 5 6	0 . 6	5 3	4 0	3 2	2 7	5 1	3 9	3 2	2 6	4 7	3 7	3 0	2 6	4 4	3 5	2 9	2 5	2 2	
			0 . 6	0 . 8	6 2	5 0	4 2	3 6	6 0	4 9	4 1	3 6	5 6	4 6	4 0	3 4	5 2	4 4	3 8	3 3	3 0			
			0 . 5 6	1 . 0	6 9	5 7	4 9	4 3	6 6	5 6	4 8	4 2	6 1	5 3	4 6	4 1	5 7	5 0	4 4	3 9	3 6			
				1 . 2 5	7 4	6 4	5 6	5 0	7 2	6 2	5 5	4 9	6 7	5 9	5 2	4 7	6 2	5 5	5 0	4 6	4 2			
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	2 . 0	2 . 5	7 8	7 6	6 9	6 1	5 5	7 6	6 7	6 0	5 4	7 1	6 3	5 7	5 2	6 6	6 0	5 5	5 0	4 6
				2 . 0	8 4	7 6	6 9	6 3	8 1	7 4	6 7	6 2	7 6	7 0	6 4	6 0	7 1	6 6	6 1	5 7	5 3			
				2 . 5	8 8	8 0	7 4	6 9	8 5	7 8	7 3	6 8	7 9	7 4	6 9	6 5	7 4	7 0	6 6	6 2	5 7			
				3 . 0	9 0	8 4	7 8	7 3	8 7	8 1	7 6	7 2	8 2	7 7	7 3	6 9	7 7	7 3	6 9	6 6	6 1			
H m	1 . 3 0 H m	1 . 3 0 H m	4 . 0	9 4	8 8	8 4	7 9	9 1	8 6	8 2	7 8	8 5	8 1	7 8	7 4	8 0	7 7	7 4	7 1	6 6				
			5 . 0	9 6	9 1	8 7	8 3	9 3	8 9	8 5	8 2	8 7	8 4	8 1	7 8	8 2	8 0	7 7	7 5	6 9				
			7 . 0	9 8	9 5	9 1	8 8	9 5	9 2	8 9	8 6	9 0	8 7	8 5	8 3	8 5	8 3	8 1	7 9	7 3				
			1 0 . 0	1 0 0	9 7	9 5	9 3	9 7	9 5	9 3	9 1	9 2	9 0	8 8	8 7	8 7	8 6	8 4	8 3	7 6				

