

屋内照明器具特性	
品番 (品名)	L G B C 8 1 0 2 3
光源	LED2700_70_1440 ×1 1440.0 lm
管理番号	K0147589 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5 / 3.5 / BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		13 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		87 %																						
保守率		良 中 否	0.63	0.6	53	40	32	27	51	39	32	26	47	37	31	26	44	35	29	25	22			
			0.6	0.8	62	50	42	36	60	49	41	36	56	46	40	34	52	44	38	33	30			
			0.56	1.0	69	57	49	43	66	56	48	42	61	53	46	41	57	50	44	39	36			
				1.25	74	64	56	50	72	62	55	49	67	59	52	47	62	55	50	46	42			
下方投影面積		c m ²	1.5	78	69	61	55	76	67	60	54	71	63	57	52	66	60	55	50	46				
等価発光面積			c m ²	2.0	84	76	69	63	81	74	67	62	76	70	64	60	71	66	61	57	53			
取付 高さ	器具間隔最大限		2.5	88	80	74	69	85	78	73	68	79	74	69	65	74	70	66	62	57				
	横方向 (A)		縦方向 (B)		3.0	90	84	78	73	87	82	76	72	82	77	73	69	77	73	69	66	61		
H m	1.29 H m		1.29 H m		4.0	94	88	84	79	91	86	82	78	85	81	78	74	80	77	74	71	66		
					5.0	96	91	87	83	93	89	85	82	87	84	81	78	82	80	77	75	69		
					7.0	98	95	91	88	95	92	89	87	90	87	85	83	85	83	81	79	73		
					10.0	100	97	95	93	97	95	93	91	92	90	88	87	87	86	84	83	76		

