

屋内照明器具特性	
品番 (品名)	LGC20117
光源	LED6200_70_3699 ×1 3699.0 lm
管理番号	K0159050 (0) DB 1
BZ分類	BZ4/6.0/BZ5

器具効率		100 % 上方光束 10 % 下方光束 90 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %					10 %					10 %					10 %					0 %
			室指数	照明率 (X0.01)																				Z CM	
保守率		良 中 否	0.63	0.6	58	47	40	35	57	46	39	34	53	44	38	34	50	42	37	33	30				
			0.6	0.8	68	58	50	45	66	56	50	45	62	54	48	44	59	52	47	43	40				
			0.56	1.0	75	65	58	53	72	63	57	52	68	61	55	51	65	58	53	49	46				
				1.25	80	71	65	59	78	70	64	59	73	67	61	57	70	64	59	56	52				
下方投影面積		cm ²		1.5	84	76	69	64	81	74	68	64	77	71	66	62	73	68	64	60	56				
等価発光面積			cm ²	2.0	89	82	76	72	86	80	75	71	82	77	72	69	78	73	70	67	62				
				2.5	92	86	81	77	89	84	80	76	85	80	77	73	80	77	74	71	66				
取付高さ	器具間隔最大限			3.0	94	89	84	81	92	87	83	79	87	83	80	77	83	79	77	74	69				
	H m		1.22 H m	1.20 H m	4.0	97	93	89	86	94	91	87	84	90	87	84	81	85	83	80	78	73			
					5.0	98	95	92	89	96	93	90	87	91	89	86	84	87	85	83	81	76			
					7.0	100	98	95	93	98	96	93	91	93	91	90	88	89	87	86	85	79			
					10.0	102	100	98	96	100	98	96	95	95	94	92	91	91	90	88	87	82			

