

屋内照明器具特性	
品番 (品名)	L G C 2 1 1 2 8
光源	LED6200_70_3450 ×1 3450.0 lm
管理番号	K0163472 (0) D 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %					
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %	
上方光束		1 1 %	室指数	照明率 (X 0 . 0 1)																				Z C M		
下方光束		8 9 %																								
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	0 . 5 6																				
			0 . 6	0 . 6	0 . 6	0 . 5 6																				
			0 . 6	0 . 6	0 . 6	0 . 5 6																				
			0 . 5 6	0 . 5 6	0 . 5 6	0 . 5 6																				
下方投影面積		c m ²	1 . 2 5	7 6	6 5	5 8	5 2	7 3	6 4	5 6	5 1	6 8	6 0	5 4	4 9	6 4	5 7	5 2	4 8	4 4						
			1 . 5	8 0	7 0	6 3	5 7	7 7	6 8	6 2	5 6	7 2	6 5	5 9	5 4	6 8	6 2	5 7	5 2	4 8						
等価発光面積		c m ²	2 . 0	8 5	7 7	7 1	6 5	8 3	7 5	6 9	6 4	7 7	7 1	6 6	6 2	7 3	6 8	6 3	6 0	5 5						
			2 . 5	8 9	8 2	7 6	7 1	8 6	8 0	7 4	7 0	8 1	7 6	7 1	6 7	7 6	7 2	6 8	6 5	6 0						
取付 高さ	器具間隔最大限		2 . 5	8 9	8 2	7 6	7 1	8 6	8 0	7 4	7 0	8 1	7 6	7 1	6 7	7 6	7 2	6 8	6 5	6 0						
	横方向 (A)		3 . 0	9 1	8 5	8 0	7 5	8 9	8 3	7 8	7 4	8 4	7 9	7 5	7 1	7 9	7 5	7 1	6 8	6 3						
H m	1 . 2 8 H m		4 . 0	9 5	9 0	8 5	8 1	9 2	8 7	8 3	8 0	8 7	8 3	8 0	7 7	8 2	7 9	7 6	7 4	6 8						
			5 . 0	9 7	9 2	8 9	8 5	9 4	9 0	8 7	8 3	8 9	8 6	8 3	8 0	8 4	8 2	7 9	7 7	7 1						
			7 . 0	9 9	9 6	9 3	9 0	9 6	9 3	9 1	8 8	9 1	8 9	8 7	8 5	8 7	8 5	8 3	8 1	7 5						
			1 0 . 0	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 2	9 3	9 2	9 0	8 8	8 9	8 7	8 6	8 4	7 9						

