

屋内照明器具特性	
品番 (品名)	L G C 2 1 1 4 8
光源	LED6200_70_3450 ×1 3450.0 lm
管理番号	K0168768 (0) DB 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z C M															
保守率		良 中 否	0.63	0.6	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26
			0.6	0.8	65	53	45	40	63	52	45	39	60	50	44	39	57	49	43	38	35	
			0.56	1.0	72	61	53	47	70	59	52	47	66	57	51	46	62	55	49	45	42	
			1.25	77	68	60	54	75	66	59	54	71	64	58	53	68	61	56	52	48		
下方投影面積		cm ²	1.5	82	72	65	60	79	71	64	59	75	68	63	58	72	66	61	57	53		
			2.0	87	79	73	68	85	78	72	67	81	75	70	66	77	72	68	64	60		
等価発光面積		cm ²	2.5	91	84	78	74	88	82	77	73	84	79	75	71	80	76	72	69	65		
			3.0	93	87	82	78	91	86	81	77	87	82	78	75	83	79	76	73	69		
H m	1.26 H m	1.26 H m	4.0	96	92	87	84	94	90	86	82	90	86	83	80	86	83	81	78	74		
			5.0	98	94	91	87	96	93	89	86	92	89	86	84	88	86	84	81	77		
			7.0	101	98	95	92	98	96	93	91	95	92	90	88	91	89	87	85	81		
			10.0	102	100	98	96	100	98	96	95	96	95	93	92	93	91	90	89	84		

