

屋内照明器具特性	
品番 (品名)	LGC21159
光源	LED6200_70_3699 ×1 3699.0 lm
管理番号	K0147595 (0) DB1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01)																Z	CM
保守率		良 中 否	0.63	0.6	0.6	54	42	34	29	53	41	34	28	50	40	33	28	47	38	32	27	25
			0.6	0.8	64	52	44	39	62	51	44	38	59	49	42	37	55	47	41	37	34	
			0.56	1.0	71	60	52	46	69	58	51	45	65	56	49	44	61	53	48	43	40	
				1.25	77	66	59	53	74	65	58	52	70	62	56	51	66	60	54	50	46	
下方投影面積 等価発光面積		cm ²	1.5	81	71	64	58	78	70	63	58	74	67	61	56	70	64	59	55	51		
			2.0	86	78	72	67	84	77	71	66	80	73	68	64	75	70	66	62	58		
			2.5	90	83	77	72	88	81	76	71	83	78	73	69	79	75	71	67	63		
取付 高さ	器具間隔最大限		3.0	92	86	81	77	90	85	80	76	86	81	77	73	81	78	74	71	67		
	横方向 (A)	縦方向 (B)	4.0	96	91	86	83	93	89	85	81	89	85	82	79	85	82	79	76	72		
H m	1.28 H m	1.28 H m	5.0	98	94	90	86	95	92	88	85	91	88	85	82	87	84	82	80	75		
			7.0	100	97	94	91	98	95	92	90	93	91	89	87	89	87	86	84	79		
			10.0	102	100	97	95	100	98	96	94	95	94	92	90	91	90	89	87	82		

