

屋内照明器具特性	
品番 (品名)	LGC35803
光源	LED6500_70_3350 ×1 3350.0 lm
管理番号	K0157434 (0) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		11 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		89 %																								
保守率		良 中 否	0.63	0.6	54	41	33	28	52	40	33	27	48	38	31	27	45	36	30	26	23					
			0.6	0.8	63	51	43	37	61	50	42	37	57	47	41	36	53	45	39	35	32					
				1.0	70	58	50	44	67	57	49	44	63	54	47	42	59	51	46	41	38					
			0.56	1.25	75	65	57	51	73	64	56	51	68	60	54	49	64	57	52	48	44					
下方投影面積		cm ²		1.5	80	70	63	57	77	68	62	56	72	65	59	54	68	62	57	52	48					
				2.0	85	77	71	65	83	75	69	64	78	72	66	62	73	68	64	60	55					
取付 高さ	器具間隔最大限			2.5	89	82	76	71	86	80	74	70	81	76	71	67	77	72	68	65	60					
	横方向 (A) 縦方向 (B)			3.0	91	85	80	75	89	83	78	74	84	79	75	71	79	75	72	69	64					
1.5m	1.96 m	1.96 m		4.0	95	90	85	81	92	88	84	80	87	83	80	77	83	79	77	74	69					
2	2.58	2.59		5.0	97	93	89	85	94	90	87	84	89	86	83	81	85	82	80	77	72					
2.5	3.14	3.14		7.0	99	96	93	90	97	94	91	89	92	89	87	85	87	85	83	82	76					
3	3.77	3.77		10.0	101	99	96	94	99	96	94	92	94	92	90	89	89	88	86	85	79					

