

屋内照明器具特性	
品番 (品名)	LGC41121
光源	LED6200_70_4899 ×1 4899.0 lm
管理番号	K0168478 (0) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.63	0.6	54	42	34	28	52	41	33	28	49	39	32	27	47	38	31	27	24				
			0.6	0.8	64	52	44	38	62	51	44	38	59	49	42	37	55	47	41	37	34				
			0.56	1.0	71	60	52	46	69	58	51	45	65	56	50	44	61	54	48	44	41				
				1.25	77	67	59	53	75	65	58	53	71	63	57	52	67	60	55	51	47				
下方投影面積		cm ²		1.5	81	72	65	59	79	70	64	58	75	68	62	57	71	65	60	56	52				
				2.0	87	79	73	68	85	78	72	67	80	74	69	65	77	72	67	64	60				
取付高さ	器具間隔最大限			2.5	91	84	78	74	88	82	77	73	84	79	75	71	80	76	72	69	65				
	横方向 (A)	縦方向 (B)		3.0	93	87	82	78	91	86	81	77	87	82	78	75	83	79	76	73	69				
H m	1.37 H m	1.37 H m		4.0	96	92	88	84	94	90	86	83	90	87	83	80	86	83	81	78	74				
				5.0	98	94	91	88	96	93	89	86	92	89	86	84	88	86	84	81	77				
				7.0	101	98	95	93	99	96	93	91	95	92	90	88	91	89	87	86	81				
				10.0	102	100	98	96	100	98	97	95	97	95	93	92	93	91	90	89	84				

