

屋内照明器具特性	
品番 (品名)	L G C 4 1 1 3 8
光源	LED6200_70_4650 ×1 4650.0 lm
管理番号	K0168480 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	5 3	4 0	3 2	2 7	5 2	4 0	3 2	2 6	4 9	3 8	3 1	2 6	4 6	3 7	3 0	2 6	2 3	
			0 . 6	6 3	5 1	4 3	3 6	6 1	5 0	4 2	3 6	5 8	4 8	4 1	3 5	5 4	4 6	4 0	3 5	3 2	
			1 . 0	7 0	5 8	5 0	4 4	6 8	5 7	4 9	4 3	6 4	5 5	4 8	4 2	6 0	5 2	4 6	4 2	3 9	
			0 . 5 6	1 . 2 5	7 6	6 5	5 7	5 1	7 3	6 4	5 6	5 0	6 9	6 1	5 5	4 9	6 6	5 9	5 3	4 8	4 5
下方投影面積		c m ²	1 . 5	8 0	7 0	6 3	5 7	7 8	6 9	6 2	5 6	7 3	6 6	6 0	5 5	7 0	6 3	5 8	5 3	5 0	
			等価発光面積		c m ²	2 . 0	8 6	7 7	7 1	6 5	8 3	7 6	6 9	6 4	7 9	7 3	6 7	6 3	7 5	7 0	6 5
取付 高さ	器具間隔最大限		2 . 5	8 9	8 2	7 6	7 1	8 7	8 0	7 5	7 0	8 3	7 7	7 2	6 8	7 9	7 4	7 0	6 7	6 3	
	横方向 (A) 縦方向 (B)		3 . 0	9 2	8 6	8 0	7 5	9 0	8 4	7 9	7 4	8 5	8 1	7 6	7 2	8 2	7 7	7 4	7 1	6 7	
H m	1 . 3 7 H m	1 . 3 7 H m	4 . 0	9 5	9 0	8 6	8 2	9 3	8 8	8 4	8 0	8 9	8 5	8 1	7 8	8 5	8 2	7 9	7 6	7 2	
			5 . 0	9 7	9 3	8 9	8 6	9 5	9 1	8 8	8 4	9 1	8 8	8 5	8 2	8 7	8 5	8 2	8 0	7 5	
			7 . 0	1 0 0	9 7	9 4	9 1	9 8	9 5	9 2	8 9	9 4	9 1	8 9	8 7	9 0	8 8	8 6	8 4	8 0	
			1 0 . 0	1 0 2	9 9	9 7	9 5	1 0 0	9 8	9 5	9 3	9 6	9 4	9 2	9 1	9 2	9 1	8 9	8 8	8 3	

