

屋内照明器具特性	
品番 (品名)	L G C 4 1 1 4 6
光源	LED6200_70_4550 ×1 4550.0 lm
管理番号	K0168768 (0) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		6 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		9 4 %																					
保守率		良 中 否	0 . 6 3	0 . 6	5 5	4 3	3 5	3 0	5 4	4 2	3 5	2 9	5 1	4 1	3 4	2 9	4 8	3 9	3 3	2 9	2 6		
			0 . 6	0 . 8	6 5	5 3	4 5	4 0	6 3	5 2	4 5	3 9	6 0	5 0	4 4	3 9	5 7	4 9	4 3	3 8	3 5		
			0 . 5 6	1 . 0	7 2	6 1	5 3	4 7	7 0	5 9	5 2	4 7	6 6	5 7	5 1	4 6	6 2	5 5	4 9	4 5	4 2		
				1 . 2 5	7 7	6 8	6 0	5 4	7 5	6 6	5 9	5 4	7 1	6 4	5 8	5 3	6 8	6 1	5 6	5 2	4 8		
下方投影面積		c m ²	1 . 5	8 2	7 2	6 5	6 0	7 9	7 1	6 4	5 9	7 5	6 8	6 3	5 8	7 2	6 6	6 1	5 7	5 3			
			2 . 0	8 7	7 9	7 3	6 8	8 5	7 8	7 2	6 7	8 1	7 5	7 0	6 6	7 7	7 2	6 8	6 4	6 0			
取付高さ	器具間隔最大限		2 . 5	9 1	8 4	7 8	7 4	8 8	8 2	7 7	7 3	8 4	7 9	7 5	7 1	8 0	7 6	7 2	6 9	6 5			
	横方向 (A)		縦方向 (B)	3 . 0	9 3	8 7	8 2	7 8	9 1	8 6	8 1	7 7	8 7	8 2	7 8	7 5	8 3	7 9	7 6	7 3	6 9		
H m	1 . 2 6 H m	1 . 2 6 H m	4 . 0	9 6	9 2	8 7	8 4	9 4	9 0	8 6	8 2	9 0	8 6	8 3	8 0	8 6	8 3	8 1	7 8	7 4			
			5 . 0	9 8	9 4	9 1	8 7	9 6	9 3	8 9	8 6	9 2	8 9	8 6	8 4	8 8	8 6	8 4	8 1	7 7			
			7 . 0	1 0 1	9 8	9 5	9 2	9 8	9 6	9 3	9 1	9 5	9 2	9 0	8 8	9 1	8 9	8 7	8 5	8 1			
			1 0 . 0	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 6	9 5	9 3	9 2	9 3	9 1	9 0	8 9	8 4			

