

屋内照明器具特性	
品番 (品名)	LGC45801
光源	LED6500_70_4300 ×1 4300.0lm
管理番号	K0157427 (0) DB1
BZ分類	BZ5/8.5/BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		16 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		84 %																								
保守率		良 中 否	0.63	0.6	53	41	33	27	51	39	32	27	47	37	31	26	43	35	29	25	22					
			0.6	0.8	62	50	42	37	60	49	41	36	55	46	39	34	51	43	37	33	30					
				1.0	69	57	49	43	66	56	48	42	61	52	46	41	56	49	43	39	35					
			0.56	1.25	74	64	56	50	71	62	55	49	66	58	52	47	61	55	49	45	41					
下方投影面積		cm ²		1.5	78	69	62	56	75	67	60	54	70	63	57	52	65	59	54	50	45					
				2.0	84	76	69	64	81	73	67	62	75	69	64	59	70	65	60	57	51					
等価発光面積		cm ²		2.5	87	80	74	69	84	78	72	68	78	73	69	65	73	69	65	61	56					
				3.0	90	84	78	74	87	81	76	72	81	76	72	68	75	72	68	65	59					
1.5m		1.96 m	1.96 m	4.0	93	88	84	80	90	86	81	78	84	80	77	74	79	76	73	70	64					
2		2.59	2.58	5.0	95	91	87	84	92	88	85	81	86	83	80	77	81	78	76	73	67					
2.5		3.22	3.22	7.0	98	94	91	88	95	92	89	86	89	86	84	82	83	81	79	78	71					
3		3.76	3.76	10.0	100	97	95	93	97	94	92	90	91	89	87	86	85	84	82	81	74					

