

屋内照明器具特性	
品番 (品名)	L G C 4 8 1 0 0
光源	LED6200_70_4899 ×1 4899.0 lm
管理番号	K0168345 (0) DB 1
B Z 分類	BZ6 / 0.9 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		2 4 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		7 6 %																					
保守率		良 中 否	0 . 6 3	0 . 6	5 1	3 9	3 1	2 5	4 8	3 7	3 0	2 4	4 4	3 4	2 8	2 3	3 9	3 1	2 6	2 2	1 8		
			0 . 6	0 . 8	6 0	4 9	4 1	3 5	5 8	4 7	3 9	3 4	5 2	4 3	3 7	3 2	4 7	4 0	3 4	3 0	2 6		
			0 . 5 6	1 . 0	6 7	5 6	4 8	4 2	6 4	5 4	4 6	4 1	5 8	4 9	4 3	3 8	5 2	4 5	4 0	3 6	3 1		
				1 . 2 5	7 3	6 3	5 5	4 9	6 9	6 0	5 3	4 8	6 3	5 5	5 0	4 5	5 7	5 1	4 6	4 2	3 6		
下方投影面積		c m ²		1 . 5	7 7	6 8	6 0	5 5	7 4	6 5	5 8	5 3	6 7	6 0	5 4	5 0	6 1	5 5	5 0	4 7	4 1		
等価発光面積			c m ²	2 . 0	8 3	7 5	6 8	6 3	7 9	7 2	6 6	6 1	7 2	6 6	6 1	5 7	6 6	6 1	5 7	5 4	4 7		
取付 高さ	器具間隔最大限		2 . 5	8 6	8 0	7 4	6 9	8 3	7 6	7 1	6 7	7 6	7 1	6 6	6 2	6 9	6 5	6 1	5 8	5 1			
	横方向 (A)		縦方向 (B)	3 . 0	8 9	8 3	7 8	7 3	8 5	8 0	7 5	7 1	7 8	7 4	7 0	6 6	7 1	6 8	6 5	6 2	5 4		
H m	1 . 4 2 H m	1 . 4 2 H m	4 . 0	9 2	8 7	8 3	7 9	8 8	8 4	8 0	7 7	8 1	7 8	7 5	7 2	7 4	7 2	6 9	6 7	5 9			
			5 . 0	9 4	9 0	8 7	8 3	9 0	8 7	8 3	8 0	8 3	8 0	7 8	7 5	7 6	7 4	7 2	7 0	6 2			
			7 . 0	9 7	9 4	9 1	8 8	9 3	9 0	8 8	8 5	8 6	8 3	8 1	7 9	7 9	7 7	7 5	7 4	6 5			
			1 0 . 0	9 8	9 6	9 4	9 2	9 5	9 3	9 1	8 9	8 7	8 6	8 4	8 3	8 1	7 9	7 8	7 7	6 8			

