

屋内照明器具特性	
品番 (品名)	L S E B C 2 0 6 1
光源	LED2700_70_1440 ×1 1440.0 lm
管理番号	K0189502 (0) D 1
B Z 分類	BZ5 / 8.5 / BZ6

器具効率		100 % 上方光束 10 % 下方光束 90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z CM															
保守率		良 中 否	0.63	0.6	54	41	33	28	52	40	33	28	48	38	32	27	45	37	31	26	24	
			0.6	0.8	63	51	43	37	61	50	42	37	57	48	41	36	53	45	39	35	32	
			0.56	1.0	70	58	50	44	67	57	49	44	63	54	48	42	59	51	46	41	38	
			1.25	75	65	57	51	73	63	56	50	68	60	54	49	64	57	52	48	44		
下方投影面積		cm ²	1.5	79	70	62	57	77	68	61	56	72	65	59	54	68	62	57	52	48		
等価発光面積			cm ²	2.0	85	77	70	65	82	75	69	64	78	71	66	62	73	68	63	59		
				2.5	89	81	75	70	86	79	74	69	81	76	71	67	76	72	68	64		
取付 高さ	器具間隔最大限		3.0	91	85	79	75	89	83	78	73	84	79	75	71	79	75	71	68	63		
	横方向 (A)		縦方向 (B)		4.0	94	89	85	81	92	87	83	79	87	83	79	76	82	79	76		
H m	1.27 H m		1.27 H m		5.0	96	92	88	85	94	90	86	83	89	86	83	80	84	82	79		
					7.0	99	96	92	90	96	93	90	88	92	89	87	84	87	85	83		
					10.0	101	98	96	94	98	96	94	92	94	92	90	88	89	88	86		

