

屋内照明器具特性	
品番 (品名)	L S E W4 0 0 0 WU
光源	LDA4 L - H - E17 / E / S / W / 2 × 1 440.0 l m
管理番号	K0123403 (1) DB 1
BZ分類	BZ9 / 3.5 / BZ8

器具効率		57 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %					10 %					10 %					0 %	
上方光束		24 %	室指数	照明率 (X0.01)																				Z	C	M
下方光束		33 %																								
保守率		良 中 否	0.63	0.6	25	18	13	10	23	16	12	9	19	14	10	8	16	11	8	6	4					
			0.6	0.8	30	23	18	14	27	21	16	13	23	18	14	11	19	15	12	9	6					
			0.56	1.0	33	26	21	17	31	24	20	16	26	21	17	14	21	17	14	12	8					
				1.25	36	30	25	21	34	28	23	20	28	24	20	17	23	20	17	14	10					
下方投影面積		c m ²		1.5	39	33	28	24	36	30	26	22	30	26	22	19	25	22	19	16	11					
等価発光面積			c m ²	2.0	42	37	32	29	39	34	30	27	33	29	26	23	27	24	22	20	14					
取付	器具間隔最大限			2.5	44	39	35	32	41	37	33	30	35	31	29	26	29	27	24	22	16					
高さ	横方向 (A)		縦方向 (B)	3.0	46	42	38	35	43	39	35	32	36	33	31	28	31	28	26	24	17					
H m	1.59 H m	2.31 H m	4.0	48	44	41	38	45	41	38	36	38	36	33	31	32	30	28	27	20						
			5.0	49	46	43	41	46	43	41	38	40	37	35	33	34	32	30	29	21						
			7.0	51	48	46	44	48	45	43	41	41	39	38	36	35	34	32	31	24						
			10.0	52	50	49	47	49	47	46	44	43	41	40	39	36	35	34	33	25						

