

屋内照明器具特性

品番 (品名)		L S S 1 2 - 4 - 6 2 - 4 0 K (X F X 4 6 0 N E W																				
光源		L E D 4 0 0 0 _ 8 5 _ 6 7 0 0 × 1 6 7 0 0 . 0 l m																				
管理番号		K 0 1 9 2 4 4 7 (0) D R 1																				
B Z 分類		B Z 5																				
器具効率 上方光束 下方光束		1 0 0 % 4 % 9 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
					室指数	照明率 (X 0 . 0 1)																
保守率		良 中 否	0 . 8 3	0 . 6	5 5	4 3	3 5	3 0	5 4	4 2	3 5	3 0	5 1	4 1	3 4	2 9	4 9	4 0	3 3	2 9	2 7	
			0 . 8 1	0 . 8	6 5	5 4	4 6	4 0	6 3	5 3	4 5	3 9	6 0	5 1	4 4	3 9	5 7	4 9	4 3	3 8	3 6	
			0 . 7 7	1 . 0	7 2	6 1	5 3	4 7	7 0	6 0	5 2	4 7	6 6	5 8	5 1	4 6	6 3	5 6	5 0	4 5	4 2	
				1 . 2 5	7 8	6 8	6 0	5 4	7 6	6 6	5 9	5 4	7 2	6 4	5 8	5 3	6 8	6 2	5 6	5 2	4 9	
下方投影面積		c m ²	1 . 5	8 2	7 2	6 5	6 0	8 0	7 1	6 4	5 9	7 6	6 9	6 3	5 8	7 2	6 6	6 1	5 7	5 4		
等価発光面積			c m ²	2 . 0	8 7	7 9	7 3	6 8	8 5	7 8	7 2	6 7	8 1	7 5	7 0	6 6	7 8	7 3	6 8	6 4	6 1	
取付高さ		器具間隔最大限		2 . 5	9 1	8 4	7 8	7 3	8 9	8 3	7 7	7 3	8 5	8 0	7 5	7 1	8 1	7 7	7 3	7 0	6 6	
		横方向 (A) 縦方向 (B)		3 . 0	9 3	8 7	8 2	7 8	9 1	8 6	8 1	7 7	8 7	8 3	7 9	7 5	8 4	8 0	7 7	7 3	7 0	
1 . 5 m		1 . 9 6 m	2 . 1 m	4 . 0	9 6	9 2	8 7	8 4	9 4	9 0	8 6	8 3	9 1	8 7	8 4	8 1	8 7	8 4	8 1	7 9	7 5	
2		2 . 5 8	2 . 6 4	5 . 0	9 8	9 4	9 1	8 7	9 7	9 3	8 9	8 6	9 3	9 0	8 7	8 4	8 9	8 7	8 4	8 2	7 8	
2 . 5		3 . 2 1	3 . 2	7 . 0	1 0 1	9 8	9 5	9 2	9 9	9 6	9 3	9 1	9 5	9 3	9 1	8 9	9 2	9 0	8 8	8 6	8 2	
3		3 . 8 4	3 . 7 7	1 0 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 7	9 6	9 4	9 2	9 4	9 2	9 1	9 0	8 6	

