

屋内照明器具特性	
品番 (品名)	NNCF21135J (J Y O U J I _ C E I L I N
光源	LED5000_85_2800 ×1 2800.0 l m
管理番号	K0194930 (0) DR 1
B Z 分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.83	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	28	26
			0.81	0.8	65	54	46	40	63	52	45	39	60	50	44	39	57	49	43	38	35
			0.77	1.0	72	61	53	47	70	60	52	47	66	57	51	46	63	55	50	45	42
				1.25	78	68	61	55	76	67	60	54	72	64	58	53	68	61	56	52	49
下方投影面積		cm ²		1.5	82	73	66	60	80	71	65	60	76	69	63	58	72	66	61	57	54
			等価発光面積	cm ²	2.0	88	80	74	69	85	78	73	68	81	75	71	66	77	73	68	65
取付 高さ	器具間隔最大限		2.5	91	85	79	75	89	83	78	74	85	80	76	72	81	77	73	70	66	
	横方向 (A) 縦方向 (B)			3.0	94	88	83	79	91	86	82	78	87	83	79	76	83	80	77	74	70
1.5m	1.98 m	1.97 m	4.0	97	92	88	85	95	90	87	83	91	87	84	81	87	84	81	79	75	
2	2.63	2.59	5.0	99	95	92	88	97	93	90	87	93	90	87	85	89	86	84	82	78	
2.5	3.29	3.21	7.0	101	98	95	93	99	96	94	92	95	93	91	89	91	90	88	86	82	
3	3.97	3.85	10.0	103	101	99	97	101	99	97	95	97	95	94	92	93	92	91	89	85	

