

屋内照明器具特性	
品番 (品名)	NNCF21135J (JYOUJI_WALL)
光源	LED5000_85_2800 ×1 2800.0 lm
管理番号	K0194242 (0) DB1
BZ分類	BZ10/8.5/BZ9

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		5 1 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		4 9 %																							
保守率		良 中 否	0 . 8 3	0 . 6	4 3	3 0	2 2	1 7	3 9	2 8	2 0	1 5	3 2	2 3	1 7	1 2	2 5	1 8	1 3	9	4				
			0 . 8 1	0 . 8	5 1	3 9	3 0	2 4	4 7	3 5	2 7	2 2	3 8	2 9	2 3	1 8	3 0	2 3	1 8	1 4	7				
			0 . 7 7	1 . 0	5 7	4 5	3 6	2 9	5 2	4 1	3 3	2 7	4 2	3 4	2 7	2 2	3 3	2 7	2 2	1 8	1 0				
			1 . 2 5	6 3	5 1	4 2	3 6	5 7	4 7	3 9	3 3	4 6	3 8	3 2	2 7	3 7	3 1	2 6	2 2	1 2					
下方投影面積		c m ²	1 . 5	6 7	5 6	4 8	4 1	6 1	5 1	4 4	3 8	5 0	4 2	3 6	3 1	4 0	3 4	2 9	2 5	1 5					
等価発光面積			c m ²	2 . 0	7 3	6 3	5 5	4 9	6 6	5 8	5 1	4 5	5 5	4 8	4 2	3 8	4 4	3 9	3 4	3 1	1 9				
取付 高さ	器具間隔最大限		2 . 5	7 6	6 8	6 1	5 5	7 0	6 2	5 6	5 1	5 8	5 2	4 7	4 2	4 7	4 2	3 8	3 5	2 2					
	横方向 (A)		縦方向 (B)		3 . 0	7 9	7 1	6 5	5 9	7 3	6 6	6 0	5 5	6 0	5 5	5 0	4 6	4 9	4 5	4 1	3 8	2 4			
1 . 5m	0	m	1 . 9 5	m	4 . 0	8 3	7 6	7 1	6 6	7 6	7 0	6 5	6 1	6 4	5 9	5 5	5 1	5 2	4 8	4 5	4 2	2 8			
2	0		2 . 5 5		5 . 0	8 5	8 0	7 5	7 0	7 8	7 4	6 9	6 5	6 6	6 2	5 8	5 5	5 4	5 1	4 8	4 5	3 1			
2 . 5	0		3 . 1 5		7 . 0	8 8	8 4	8 0	7 6	8 1	7 7	7 4	7 0	6 9	6 5	6 3	6 0	5 6	5 4	5 2	5 0	3 4			
3	0		3 . 7 6		1 0 . 0	9 0	8 7	8 4	8 1	8 4	8 1	7 8	7 5	7 1	6 8	6 6	6 4	5 9	5 7	5 5	5 3	3 7			

