

屋内照明器具特性	
品番 (品名)	NNCF22115 (J Y O U J I _ C E I L I N G
光源	LED5000_85_1600 ×1 1600.0 l m
管理番号	K0185375 (1) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		8 %	室指数	照明率 (X 0 . 0 1) Z C M																					
下方光束		9 2 %																							
保守率		良 中 否	0 . 8 3	0 . 6	5 5	4 2	3 4	2 9	5 3	4 1	3 4	2 9	5 0	4 0	3 3	2 8	4 7	3 8	3 2	2 8	2 5				
			0 . 8 1	0 . 8	6 4	5 3	4 5	3 9	6 2	5 2	4 4	3 9	5 9	4 9	4 3	3 8	5 5	4 7	4 1	3 7	3 4				
			0 . 7 7	1 . 0	7 1	6 0	5 2	4 6	6 9	5 9	5 1	4 6	6 5	5 6	5 0	4 5	6 1	5 4	4 8	4 4	4 1				
				1 . 2 5	7 7	6 7	6 0	5 4	7 5	6 6	5 9	5 3	7 0	6 3	5 7	5 2	6 7	6 0	5 5	5 1	4 7				
下方投影面積		cm ²	1 . 5	8 1	7 2	6 5	5 9	7 9	7 0	6 4	5 9	7 4	6 7	6 2	5 7	7 0	6 4	6 0	5 6	5 2					
等価発光面積		cm ²	2 . 0	8 7	7 9	7 3	6 8	8 4	7 7	7 2	6 7	8 0	7 4	6 9	6 5	7 6	7 1	6 7	6 3	5 9					
取付高さ	器具間隔最大限		2 . 5	9 0	8 4	7 8	7 4	8 8	8 2	7 7	7 2	8 3	7 8	7 4	7 0	7 9	7 5	7 1	6 8	6 4					
	横方向 (A) 縦方向 (B)		3 . 0	9 3	8 7	8 2	7 8	9 0	8 5	8 1	7 7	8 6	8 2	7 8	7 4	8 2	7 8	7 5	7 2	6 8					
1 . 5m	2 m	1 . 9 5 m	4 . 0	9 6	9 1	8 7	8 4	9 4	8 9	8 6	8 2	8 9	8 6	8 3	8 0	8 5	8 2	8 0	7 7	7 3					
2	2 . 6 2	2 . 5 3	5 . 0	9 8	9 4	9 1	8 7	9 6	9 2	8 9	8 6	9 1	8 8	8 6	8 3	8 7	8 5	8 2	8 0	7 6					
2 . 5	3 . 2 9	3 . 1 5	7 . 0	1 0 0	9 7	9 5	9 2	9 8	9 5	9 3	9 1	9 4	9 1	8 9	8 7	9 0	8 8	8 6	8 4	8 0					
3	3 . 9 5	3 . 7 7	1 0 . 0	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 4	9 6	9 4	9 2	9 1	9 2	9 0	8 9	8 8	8 3					

