

屋内照明器具特性	
品番 (品名)	NNF 4 1 8 8 7
光源	LED_BASE3500_85_3050 ×1 3050.0 lm
管理番号	K0157494 (0) DB 1
B Z 分類	BZ2 / 1.8 / BZ3 / 3.5 / BZ4 / 6.0 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		1 0 0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		0 %		室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 8 3	0 . 6	4 3	3 3	2 6	2 2	3 7	2 8	2 3	1 9	2 5	2 0	1 6	1 3	1 4	1 1	9	8	0
			0 . 8 1	0 . 8	5 1	4 1	3 4	2 9	4 3	3 5	3 0	2 6	3 0	2 4	2 1	1 8	1 7	1 4	1 2	1 1	0
			1 . 0	1 . 0	5 7	4 7	4 1	3 6	4 8	4 1	3 5	3 1	3 3	2 8	2 5	2 2	1 9	1 6	1 4	1 3	0
			0 . 7 7	1 . 2 5	6 2	5 3	4 7	4 2	5 3	4 6	4 0	3 6	3 6	3 2	2 8	2 6	2 1	1 8	1 7	1 5	0
下方投影面積		cm ²	1 . 5	6 5	5 7	5 1	4 7	5 6	5 0	4 5	4 1	3 8	3 4	3 1	2 9	2 2	2 0	1 8	1 7	0	
等価発光面積		cm ²	2 . 0	7 0	6 4	5 8	5 4	6 0	5 5	5 1	4 7	4 1	3 8	3 5	3 3	2 4	2 2	2 1	2 0	0	
取付 高さ	器具間隔最大限		2 . 5	7 3	6 8	6 3	5 9	6 3	5 8	5 5	5 1	4 3	4 1	3 8	3 6	2 5	2 4	2 2	2 1	0	
	横方向 (A)	縦方向 (B)	3 . 0	7 5	7 0	6 6	6 3	6 5	6 1	5 7	5 4	4 5	4 2	4 0	3 8	2 6	2 5	2 4	2 3	0	
1 . 5m	1 . 8 m	1 . 7 3 m	4 . 0	7 8	7 4	7 1	6 8	6 7	6 4	6 1	5 9	4 6	4 5	4 3	4 1	2 7	2 6	2 5	2 4	0	
2	2 . 4	2 . 2 2	5 . 0	8 0	7 6	7 4	7 1	6 9	6 6	6 4	6 2	4 8	4 6	4 5	4 3	2 8	2 7	2 6	2 6	0	
2 . 5	2 . 9 9	2 . 8	7 . 0	8 2	7 9	7 7	7 5	7 0	6 9	6 7	6 5	4 9	4 8	4 7	4 6	2 9	2 8	2 7	2 7	0	
3	3 . 5 8	3 . 3 7	1 0 . 0	8 3	8 1	8 0	7 8	7 2	7 0	6 9	6 8	5 0	4 9	4 8	4 8	2 9	2 9	2 8	2 8	0	

