

屋内照明器具特性	
品番 (品名)	NNF 4 2 2 3 0
光源	LDL40S. N/ 19/ 25- K ×2 2500.0 lm
管理番号	K0126286 (1) DR 1
B Z 分類	BZ6/ 1. 4/ BZ5/ 1. 8/ BZ6/ 2. 3/ BZ5 / 3. 5/ BZ6/ 4. 5/ BZ5

器具効率			95 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
						床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) ZCM																	
保守率			良 中 否	0.81	0.6	51	38	31	25	49	38	30	25	47	37	30	25	44	35	29	25	23	
				0.77	0.8	60	48	40	34	58	47	40	34	55	46	39	34	53	44	38	33	31	
				1.0	1.0	66	55	47	41	64	54	46	41	61	52	45	40	58	50	44	40	37	
				0.68	1.25	72	61	54	48	70	60	53	47	67	58	52	47	64	56	51	46	44	
下方投影面積			cm ²	1.5	76	66	59	53	74	65	58	53	71	63	57	52	67	61	56	51	48		
				等価発光面積			cm ²	2.0	81	73	67	61	80	72	66	61	76	70	64	60	73	67	63
取付高さ		器具間隔最大限			2.5	85	78	72	67	83	77	71	66	80	74	69	65	77	72	68	64	61	
		横方向 (A)		縦方向 (B)	3.0	88	81	76	71	86	80	75	71	82	78	73	69	79	75	71	68	65	
1.5m		2.14 m		2.19 m	4.0	91	86	81	77	89	85	80	77	86	82	78	75	83	80	77	74	71	
2		2.83		2.76	5.0	93	89	85	81	91	87	84	81	88	85	82	79	85	82	80	77	74	
2.5		3.52		3.36	7.0	96	92	89	86	94	91	88	85	91	88	86	84	88	86	84	82	79	
3		4.21		3.96	10.0	97	95	93	91	96	94	92	90	93	91	89	88	90	89	87	86	83	

