

屋内照明器具特性	
品番 (品名)	NNF 4 2 6 6 6
光源	LDL40S. N/ 14 / 26 (2 6 0 0 A) × 2 2 6 0 0 . 0 l m
管理番号	K0126620 (8) DB 1
B Z 分類	BZ5 / 0 . 7 / BZ4

器具効率		9 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		9 0 %																				
保守率		良 中 否	0 . 8 1	0 . 6	5 1	4 1	3 4	2 9	5 0	4 0	3 3	2 9	4 8	3 9	3 3	2 9	4 6	3 8	3 3	2 8	2 7	
			0 . 7 7	0 . 8	6 1	5 1	4 4	3 9	6 0	5 0	4 4	3 9	5 7	4 9	4 3	3 9	5 5	4 8	4 2	3 8	3 6	
			0 . 6 8	1 . 0	6 7	5 8	5 1	4 6	6 6	5 7	5 1	4 6	6 3	5 6	5 0	4 6	6 1	5 4	4 9	4 5	4 3	
				1 . 2 5	7 3	6 4	5 8	5 3	7 1	6 3	5 8	5 3	6 9	6 2	5 7	5 2	6 6	6 0	5 6	5 2	5 0	
下方投影面積		cm ²	1 . 5	7 6	6 9	6 3	5 8	7 5	6 8	6 2	5 8	7 2	6 6	6 1	5 7	7 0	6 5	6 0	5 7	5 5		
等価発光面積		cm ²	2 . 0	8 1	7 5	7 0	6 6	8 0	7 4	6 9	6 5	7 7	7 2	6 8	6 5	7 5	7 1	6 7	6 4	6 2		
取付 高さ	器具間隔最大限		2 . 5	8 4	7 9	7 5	7 1	8 3	7 8	7 4	7 0	8 0	7 6	7 3	7 0	7 8	7 5	7 1	6 9	6 6		
	横方向 (A)	縦方向 (B)	3 . 0	8 7	8 2	7 8	7 5	8 5	8 1	7 7	7 4	8 3	7 9	7 6	7 3	8 0	7 7	7 5	7 2	7 0		
1 . 5m	2 . 0 9 m	2 . 1 8 m	4 . 0	8 9	8 6	8 2	8 0	8 8	8 5	8 2	7 9	8 5	8 3	8 0	7 8	8 3	8 1	7 9	7 7	7 4		
2	2 . 7 6	2 . 7 5	5 . 0	9 1	8 8	8 5	8 3	9 0	8 7	8 4	8 2	8 7	8 5	8 3	8 1	8 5	8 3	8 1	7 9	7 7		
2 . 5	3 . 4 3	3 . 3 4	7 . 0	9 3	9 0	8 8	8 7	9 1	8 9	8 8	8 6	8 9	8 7	8 6	8 4	8 7	8 5	8 4	8 3	8 0		
3	4 . 0 9	3 . 9 4	1 0 . 0	9 4	9 2	9 1	9 0	9 3	9 1	9 0	8 9	9 1	8 9	8 8	8 7	8 8	8 7	8 6	8 6	8 3		

