

屋内照明器具特性	
品番 (品名)	N N F W4 1 0 0 1
光源	LDL40S. N/ 29/ 31- 9 (3150 A) ×1 3150.0 l m
管理番号	K0125025 (0) DR 1
B Z 分類	BZ6/ 0.7/ BZ5/ 8.5/ BZ6

器具効率		9 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 9 3	0 . 6	5 1	3 9	3 1	2 6	4 9	3 8	3 1	2 5	4 6	3 6	2 9	2 5	4 3	3 4	2 8	2 4	2 2
			0 . 9	0 . 8	6 0	4 8	4 1	3 5	5 8	4 7	4 0	3 4	5 4	4 5	3 8	3 3	5 0	4 3	3 7	3 2	2 9
			0 . 8 6	1 . 0	6 6	5 5	4 7	4 2	6 4	5 4	4 6	4 1	5 9	5 1	4 5	4 0	5 6	4 8	4 3	3 8	3 5
				1 . 2 5	7 2	6 2	5 4	4 8	6 9	6 0	5 3	4 8	6 5	5 7	5 1	4 6	6 1	5 4	4 9	4 5	4 1
下方投影面積		c m ²	1 . 5	7 6	6 6	5 9	5 3	7 3	6 5	5 8	5 3	6 8	6 1	5 6	5 1	6 4	5 8	5 3	4 9	4 5	
			等価発光面積	c m ²	2 . 0	8 1	7 3	6 7	6 1	7 9	7 1	6 5	6 0	7 4	6 8	6 3	5 8	6 9	6 4	6 0	5 6
取付高さ	器具間隔最大限		2 . 5	8 5	7 8	7 2	6 7	8 2	7 6	7 0	6 6	7 7	7 2	6 7	6 3	7 3	6 8	6 4	6 1	5 6	
	横方向 (A)	縦方向 (B)	3 . 0	8 7	8 1	7 6	7 1	8 4	7 9	7 4	7 0	8 0	7 5	7 1	6 7	7 5	7 1	6 8	6 5	6 0	
1 . 5m	2 . 1 m	2 . 0 9 m	4 . 0	9 0	8 5	8 1	7 7	8 8	8 3	7 9	7 5	8 3	7 9	7 6	7 2	7 8	7 5	7 2	7 0	6 5	
2	2 . 7 6	2 . 6 3	5 . 0	9 2	8 8	8 4	8 1	9 0	8 6	8 2	7 9	8 5	8 2	7 9	7 6	8 0	7 8	7 5	7 3	6 8	
2 . 5	3 . 4 4	3 . 1 9	7 . 0	9 5	9 1	8 8	8 6	9 2	8 9	8 6	8 4	8 7	8 5	8 3	8 0	8 3	8 1	7 9	7 7	7 2	
3	4 . 1	3 . 7 6	1 0 . 0	9 6	9 4	9 2	9 0	9 4	9 2	9 0	8 8	8 9	8 7	8 6	8 4	8 5	8 3	8 2	8 1	7 5	

