

屋内照明器具特性	
品番 (品名)	N N F W4 1 0 5 1
光源	LDL40S. N/ 14/ 26 (2600A) ×1 2600.0 lm
管理番号	K0133897 (*) DB 1
B Z 分類	B Z 6

器具効率		97 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		19 %	室指数	照明率 (X0.01) Z C M																		
下方光束		78 %																				
保守率		良 中 否	0.83	0.6	49	36	28	23	46	35	28	22	42	32	26	21	38	30	24	20	17	
			0.81	0.8	58	46	37	31	55	44	36	30	50	40	34	29	45	37	32	27	23	
			0.77	1.0	64	52	44	38	61	50	42	37	55	46	40	35	50	43	37	33	28	
				1.25	69	59	50	44	66	56	49	43	60	52	46	40	54	48	42	38	33	
下方投影面積		c m ²		1.5	73	63	56	49	70	61	54	48	64	56	50	45	58	52	47	42	37	
等価発光面積			c m ²	2.0	79	70	63	57	75	67	61	56	69	62	57	52	63	57	53	49	43	
取付 高さ	器具間隔最大限		2.5	82	75	68	63	79	72	66	61	72	66	62	57	66	61	57	54	47		
	横方向 (A) 縦方向 (B)		3.0	85	78	72	67	81	75	70	65	75	70	65	61	68	64	61	57	51		
1.5m	2.2 m	2.16 m	4.0	88	83	78	73	85	80	75	71	78	74	70	67	72	68	65	62	55		
2	2.9	2.71	5.0	90	86	81	77	87	83	79	75	80	77	73	70	74	71	68	66	58		
2.5	3.61	3.3	7.0	93	89	86	83	90	86	83	80	83	80	77	75	77	74	72	70	62		
3	4.31	3.89	10.0	95	92	90	87	92	89	87	84	85	83	81	79	79	77	75	74	66		

