

屋内照明器具特性	
品番 (品名)	N N F W4 1 0 5 1
光源	LDL40S. N / 29 / 31 - 9 (3150 A) × 1 3150.0 l m
管理番号	K0125029 (1) DR 1
B Z 分類	BZ6 / 0.7 / BZ5 / 8.5 / BZ6

器具効率		95 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		9 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		86 %																							
保守率		良 中 否	0.93	0.6	51	39	31	26	49	38	31	25	46	36	30	25	43	34	28	24	22				
			0.9	0.8	60	48	41	35	58	47	40	34	54	45	38	33	50	43	37	32	30				
				1.0	66	55	47	41	64	54	46	41	59	51	45	40	56	48	43	39	35				
			0.86	1.25	72	62	54	48	69	60	53	47	65	57	51	46	61	54	49	45	41				
下方投影面積		cm ²	1.5	75	66	59	53	73	65	58	53	68	61	56	51	64	58	53	49	45					
			2.0	81	73	67	61	78	71	65	60	74	68	63	58	69	64	60	56	52					
取付 高さ	器具間隔最大限		2.5	84	77	72	67	82	76	70	66	77	72	67	63	73	68	64	61	57					
	横方向 (A)	縦方向 (B)	3.0	87	81	75	71	84	79	74	70	79	75	71	67	75	71	68	65	60					
1.5m	2.09 m	2.09 m	4.0	90	85	81	77	87	83	79	75	83	79	76	72	78	75	72	70	65					
2	2.76	2.63	5.0	92	88	84	81	89	86	82	79	85	82	79	76	80	78	75	73	68					
2.5	3.43	3.19	7.0	94	91	88	85	92	89	86	84	87	85	83	80	83	81	79	77	72					
3	4.09	3.76	10.0	96	94	91	89	94	92	89	88	89	87	86	84	85	83	82	81	75					

