

| 屋内照明器具特性 |                                            |
|----------|--------------------------------------------|
| 品番 (品名)  | NNF W4 1 0 7 1 C                           |
| 光源       | LDL40S. N/ 14 / 26 ( 2600A ) ×1 2600.0 l m |
| 管理番号     | K0133897 ( * ) DB 1                        |
| BZ分類     | BZ6                                        |

| 器具効率     |                 | 97 %            | 反射率  | 天井   | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------------|-----------------|------|------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                 |                 |      | 壁    | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
| 上方光束     |                 | 19 %            |      | 床    | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
| 下方光束     |                 | 78 %            |      | 室指数  | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |                 | 良<br>中<br>否     | 0.83 | 0.6  | 49                | 36 | 28 | 23 | 46   | 35 | 28 | 22 | 42   | 32 | 26 | 21 | 38   | 30 | 24 | 20 | 17  |
|          |                 |                 | 0.81 | 0.8  | 58                | 46 | 37 | 31 | 55   | 44 | 36 | 30 | 50   | 40 | 34 | 29 | 45   | 37 | 32 | 27 | 23  |
|          |                 |                 | 1.0  | 64   | 52                | 44 | 38 | 61 | 50   | 42 | 37 | 55 | 46   | 40 | 35 | 50 | 43   | 37 | 33 | 28 |     |
|          |                 |                 | 0.77 | 1.25 | 69                | 59 | 50 | 44 | 66   | 56 | 49 | 43 | 60   | 52 | 46 | 40 | 54   | 48 | 42 | 38 | 33  |
| 下方投影面積   |                 | cm <sup>2</sup> | 1.5  | 73   | 63                | 56 | 49 | 70 | 61   | 54 | 48 | 64 | 56   | 50 | 45 | 58 | 52   | 47 | 42 | 37 |     |
| 等価発光面積   |                 | cm <sup>2</sup> | 2.0  | 79   | 70                | 63 | 57 | 75 | 67   | 61 | 56 | 69 | 62   | 57 | 52 | 63 | 57   | 53 | 49 | 43 |     |
| 取付<br>高さ | 器具間隔最大限         |                 | 2.5  | 82   | 75                | 68 | 63 | 79 | 72   | 66 | 61 | 72 | 66   | 62 | 57 | 66 | 61   | 57 | 54 | 47 |     |
|          | 横方向 (A) 縦方向 (B) |                 | 3.0  | 85   | 78                | 72 | 67 | 81 | 75   | 70 | 65 | 75 | 70   | 65 | 61 | 68 | 64   | 61 | 57 | 51 |     |
| 1.5m     | 2.2 m           | 2.16 m          | 4.0  | 88   | 83                | 78 | 73 | 85 | 80   | 75 | 71 | 78 | 74   | 70 | 67 | 72 | 68   | 65 | 62 | 55 |     |
| 2        | 2.9             | 2.71            | 5.0  | 90   | 86                | 81 | 77 | 87 | 83   | 79 | 75 | 80 | 77   | 73 | 70 | 74 | 71   | 68 | 66 | 58 |     |
| 2.5      | 3.61            | 3.3             | 7.0  | 93   | 89                | 86 | 83 | 90 | 86   | 83 | 80 | 83 | 80   | 77 | 75 | 77 | 74   | 72 | 70 | 62 |     |
| 3        | 4.31            | 3.89            | 10.0 | 95   | 92                | 90 | 87 | 92 | 89   | 87 | 84 | 85 | 83   | 81 | 79 | 79 | 77   | 75 | 74 | 66 |     |

