

屋内照明器具特性

品番（品名）		NNLK41319+NNL4600HNT																			
光源		LED5000_85_4940 ×1 4940.0 l m																			
管理番号		K0137981（4）DB1																			
BZ分類		BZ5																			
器具効率 上方光束 下方光束		100 % 0 % 100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
			室指数	照明率（ X0.01） ZCM																	
保守率		良 中 否 0.81 0.77 0.68	0.6	56	44	36	31	55	43	36	30	53	42	35	30	50	41	35	30	28	
			0.8	66	55	47	41	65	54	46	41	62	53	46	41	59	51	45	40	38	
			1.0	73	62	54	48	71	61	54	48	68	60	53	48	66	58	52	48	45	
			1.25	79	69	62	56	77	68	61	56	74	66	60	55	71	65	59	55	53	
下方投影面積 等価発光面積		cm ² cm ²	1.5	83	74	67	62	82	73	67	61	78	71	66	61	76	69	64	60	58	
			2.0	89	82	75	70	87	80	75	70	84	78	73	69	81	76	72	68	66	
取付 高さ	器具間隔最大限		2.5	93	86	81	76	91	85	80	76	88	83	79	75	85	81	77	74	71	
	横方向（A）	縦方向（B）	3.0	95	90	85	81	94	88	84	80	91	86	82	79	88	84	81	78	75	
1.5m	2.01 m	2.16 m	4.0	98	94	90	87	97	93	89	86	94	91	87	85	91	88	86	83	81	
2	2.65	2.71	5.0	100	97	93	90	99	96	92	90	96	93	91	88	93	91	89	87	84	
2.5	3.29	3.29	7.0	103	100	97	95	101	99	96	94	98	96	94	93	96	94	93	91	88	
3	3.93	3.89	10.0	104	102	101	99	103	101	99	98	100	99	97	96	98	97	95	94	91	

