

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK41319 + NNL4601NN        |
| 光源       | LED5000_85_6340 ×1 6340.0 lm |
| 管理番号     | K0137981 (4) DB1             |
| BZ分類     | BZ5                          |

| 器具効率   |  |        | 100 %           |      | 反射率  | 天井                | 80 % |    |     |     | 70 % |    |     |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|--|--------|-----------------|------|------|-------------------|------|----|-----|-----|------|----|-----|----|------|----|----|----|------|----|----|----|-----|
|        |  |        |                 |      |      | 壁                 | 70   | 50 | 30  | 10  | 70   | 50 | 30  | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |  |        |                 |      |      | 床                 | 10 % |    |     |     | 10 % |    |     |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |  |        |                 |      |      | 照明率 ( X0.01 ) ZCM |      |    |     |     |      |    |     |    |      |    |    |    |      |    |    |    |     |
| 保守率    |  |        | 良<br>中<br>否     | 0.81 | 0.6  | 56                | 44   | 36 | 31  | 55  | 43   | 36 | 30  | 53 | 42   | 35 | 30 | 50 | 41   | 35 | 30 | 28 |     |
|        |  |        |                 | 0.77 | 0.8  | 66                | 55   | 47 | 41  | 65  | 54   | 46 | 41  | 62 | 53   | 46 | 41 | 59 | 51   | 45 | 40 | 38 |     |
|        |  |        |                 | 0.68 | 1.0  | 73                | 62   | 54 | 48  | 71  | 61   | 54 | 48  | 68 | 60   | 53 | 48 | 66 | 58   | 52 | 48 | 45 |     |
|        |  |        |                 |      | 1.25 | 79                | 69   | 62 | 56  | 77  | 68   | 61 | 56  | 74 | 66   | 60 | 55 | 71 | 65   | 59 | 55 | 53 |     |
| 下方投影面積 |  |        | cm <sup>2</sup> | 1.5  | 83   | 74                | 67   | 62 | 82  | 73  | 67   | 61 | 78  | 71 | 66   | 61 | 76 | 69 | 64   | 60 | 58 |    |     |
|        |  |        |                 | 2.0  | 89   | 82                | 75   | 70 | 87  | 80  | 75   | 70 | 84  | 78 | 73   | 69 | 81 | 76 | 72   | 68 | 66 |    |     |
| 等価発光面積 |  |        | cm <sup>2</sup> | 2.5  | 93   | 86                | 81   | 76 | 91  | 85  | 80   | 76 | 88  | 83 | 79   | 75 | 85 | 81 | 77   | 74 | 71 |    |     |
|        |  |        |                 | 3.0  | 95   | 90                | 85   | 81 | 94  | 88  | 84   | 80 | 91  | 86 | 82   | 79 | 88 | 84 | 81   | 78 | 75 |    |     |
| 1.5m   |  | 2.01 m | 2.16 m          | 4.0  | 98   | 94                | 90   | 87 | 97  | 93  | 89   | 86 | 94  | 91 | 87   | 85 | 91 | 88 | 86   | 83 | 81 |    |     |
| 2      |  | 2.65   | 2.71            | 5.0  | 100  | 97                | 93   | 90 | 99  | 96  | 92   | 90 | 96  | 93 | 91   | 88 | 93 | 91 | 89   | 87 | 84 |    |     |
| 2.5    |  | 3.29   | 3.29            | 7.0  | 103  | 100               | 97   | 95 | 101 | 99  | 96   | 94 | 98  | 96 | 94   | 93 | 96 | 94 | 93   | 91 | 88 |    |     |
| 3      |  | 3.93   | 3.89            | 10.0 | 104  | 102               | 101  | 99 | 103 | 101 | 99   | 98 | 100 | 99 | 97   | 96 | 98 | 97 | 95   | 94 | 91 |    |     |

