

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK41509+FSK41020+NNL46     |
| 光源       | LED3000_85_4620 ×1 4620.0 lm |
| 管理番号     | K0139114 (4) DR1             |
| BZ分類     | BZ6                          |

| 器具効率     |           | 100 %<br><br>上方光束<br>15 %<br>下方光束<br>85 % | 反射率    | 天井              | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------|-------------------------------------------|--------|-----------------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |           |                                           |        | 壁               | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |           |                                           |        | 床               | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |           |                                           |        | 室指数             | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |           | 良<br>中<br>否                               | 0.81   | 0.6             | 52                | 39 | 31 | 25 | 50   | 38 | 30 | 25 | 46   | 36 | 29 | 24 | 42   | 33 | 27 | 23 | 20  |
|          |           |                                           | 0.77   | 0.8             | 61                | 49 | 40 | 34 | 58   | 47 | 39 | 33 | 54   | 44 | 37 | 32 | 50   | 41 | 35 | 31 | 27  |
|          |           |                                           | 0.68   | 1.0             | 67                | 55 | 47 | 41 | 64   | 54 | 46 | 40 | 59   | 50 | 44 | 38 | 55   | 47 | 41 | 37 | 33  |
|          |           |                                           |        | 1.25            | 73                | 62 | 54 | 48 | 70   | 60 | 52 | 47 | 65   | 56 | 50 | 45 | 60   | 53 | 47 | 43 | 38  |
| 下方投影面積   |           | cm <sup>2</sup>                           |        | 1.5             | 77                | 67 | 59 | 53 | 74   | 65 | 57 | 52 | 68   | 61 | 54 | 49 | 63   | 57 | 52 | 47 | 42  |
|          |           |                                           | 等価発光面積 | cm <sup>2</sup> | 2.0               | 83 | 74 | 67 | 61   | 79 | 72 | 65 | 60   | 74 | 67 | 62 | 57   | 68 | 63 | 58 | 54  |
| 取付<br>高さ | 器具間隔最大限   |                                           | 2.5    | 86              | 79                | 72 | 67 | 83 | 76   | 70 | 65 | 77 | 71   | 66 | 62 | 72 | 67   | 63 | 59 | 53 |     |
|          | 横方向 ( A ) | 縦方向 ( B )                                 | 3.0    | 89              | 82                | 76 | 71 | 86 | 79   | 74 | 69 | 80 | 75   | 70 | 66 | 74 | 70   | 66 | 63 | 57 |     |
| 1.5m     | 1.67 m    | 2.16 m                                    | 4.0    | 92              | 87                | 82 | 77 | 89 | 84   | 79 | 75 | 83 | 79   | 75 | 72 | 78 | 74   | 71 | 68 | 62 |     |
| 2        | 2.21      | 2.72                                      | 5.0    | 94              | 90                | 85 | 81 | 91 | 87   | 83 | 79 | 85 | 82   | 79 | 75 | 80 | 77   | 74 | 72 | 65 |     |
| 2.5      | 2.74      | 3.3                                       | 7.0    | 97              | 93                | 90 | 87 | 94 | 91   | 87 | 84 | 88 | 85   | 83 | 80 | 83 | 80   | 78 | 76 | 70 |     |
| 3        | 3.28      | 3.9                                       | 10.0   | 99              | 96                | 94 | 91 | 96 | 94   | 91 | 89 | 90 | 88   | 86 | 84 | 85 | 83   | 82 | 80 | 73 |     |

