

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK42123 + NNL4500CNT       |
| 光源       | LED5000_85_5200 ×1 5200.0 lm |
| 管理番号     | K0130919 (＊) DB1             |
| BZ分類     | BZ5                          |

| 器具効率   |           | 100 %           |           | 反射率             | 天井  | 80 %         |    |    |     |    | 70 % |    |    |    |    | 50 % |    |    |    |    | 30 % |    |    |    |    | 0 % |
|--------|-----------|-----------------|-----------|-----------------|-----|--------------|----|----|-----|----|------|----|----|----|----|------|----|----|----|----|------|----|----|----|----|-----|
|        |           |                 |           |                 | 壁   | 70           | 50 | 30 | 10  | 70 | 50   | 30 | 10 | 70 | 50 | 30   | 10 | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10 | 0 % |
|        |           |                 |           |                 | 床   | 10 %         |    |    |     |    | 10 % |    |    |    |    | 10 % |    |    |    |    | 10 % |    |    |    |    | 0 % |
|        |           |                 |           |                 | 室指数 | 照明率 ( X0.01) |    |    |     |    |      |    |    |    |    |      |    |    |    |    |      |    |    |    |    | ZCM |
| 保守率    |           | 良<br>中<br>否     | 0.83      | 0.6             | 55  | 42           | 34 | 29 | 53  | 42 | 34   | 29 | 51 | 40 | 33 | 28   | 48 | 39 | 33 | 28 | 26   |    |    |    |    |     |
|        |           |                 | 0.81      | 0.8             | 65  | 53           | 45 | 39 | 63  | 52 | 44   | 38 | 60 | 50 | 43 | 38   | 57 | 48 | 42 | 37 | 35   |    |    |    |    |     |
|        |           |                 | 0.77      | 1.0             | 71  | 60           | 52 | 46 | 69  | 59 | 51   | 46 | 66 | 57 | 50 | 45   | 62 | 55 | 49 | 44 | 42   |    |    |    |    |     |
|        |           |                 |           | 1.25            | 77  | 67           | 59 | 53 | 75  | 66 | 58   | 53 | 71 | 63 | 57 | 52   | 68 | 61 | 56 | 51 | 48   |    |    |    |    |     |
| 下方投影面積 |           | cm <sup>2</sup> |           | 1.5             | 81  | 72           | 65 | 59 | 79  | 70 | 64   | 58 | 75 | 68 | 62 | 57   | 72 | 66 | 60 | 56 | 53   |    |    |    |    |     |
|        |           |                 | 等価発光面積    | cm <sup>2</sup> | 2.0 | 87           | 79 | 72 | 67  | 85 | 77   | 71 | 66 | 81 | 75 | 69   | 65 | 77 | 72 | 68 | 64   | 60 |    |    |    |     |
| 取付高さ   | 器具間隔最大限   |                 |           | 2.5             | 90  | 84           | 78 | 73 | 88  | 82 | 77   | 72 | 85 | 79 | 74 | 70   | 81 | 76 | 72 | 69 | 66   |    |    |    |    |     |
|        | 横方向 ( A ) |                 | 縦方向 ( B ) | 3.0             | 93  | 87           | 82 | 77 | 91  | 85 | 80   | 76 | 87 | 82 | 78 | 75   | 84 | 80 | 76 | 73 | 69   |    |    |    |    |     |
| 1.5m   | 1.99 m    | 2.17 m          |           | 4.0             | 96  | 91           | 87 | 83 | 94  | 90 | 86   | 82 | 91 | 87 | 83 | 80   | 87 | 84 | 81 | 78 | 75   |    |    |    |    |     |
| 2      | 2.62      | 2.74            |           | 5.0             | 98  | 94           | 90 | 87 | 96  | 93 | 89   | 86 | 93 | 89 | 86 | 84   | 89 | 87 | 84 | 82 | 78   |    |    |    |    |     |
| 2.5    | 3.26      | 3.32            |           | 7.0             | 101 | 97           | 95 | 92 | 99  | 96 | 93   | 91 | 95 | 93 | 90 | 88   | 92 | 90 | 88 | 86 | 82   |    |    |    |    |     |
| 3      | 3.89      | 3.92            |           | 10.0            | 102 | 100          | 98 | 96 | 101 | 99 | 96   | 95 | 97 | 95 | 94 | 92   | 94 | 92 | 91 | 90 | 86   |    |    |    |    |     |

