

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK42722J + NNL4300ENT      |
| 光源       | LED5000_85_3100 ×1 3100.0 lm |
| 管理番号     | K0134500 (4) DB1             |
| BZ分類     | BZ5/2.3/BZ4                  |

| 器具効率   |           | 100 %           | 反射率             | 天井            | 80 % |     |    |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 %  |
|--------|-----------|-----------------|-----------------|---------------|------|-----|----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|------|
|        |           |                 |                 | 壁             | 70   | 50  | 30 | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 %  |
|        |           |                 |                 | 床             | 10 % |     |    |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 %  |
| 上方光束   |           | 0 %             | 室指数             | 照明率 ( X0.01 ) |      |     |    |     |      |     |    |     |      |    |    |    |      |    |    |    | Z CM |
| 下方光束   |           |                 |                 | 100 %         |      |     |    |     |      |     |    |     |      |    |    |    |      |    |    |    |      |
| 保守率    |           | 良<br>中<br>否     | 0.81            | 0.6           | 57   | 44  | 36 | 31  | 55   | 44  | 36 | 31  | 53   | 43 | 36 | 31 | 51   | 42 | 35 | 31 | 29   |
|        |           |                 | 0.77            | 0.8           | 67   | 55  | 47 | 42  | 65   | 55  | 47 | 42  | 63   | 53 | 46 | 41 | 60   | 52 | 46 | 41 | 39   |
|        |           |                 | 0.68            | 1.0           | 74   | 63  | 55 | 49  | 72   | 62  | 55 | 49  | 69   | 60 | 54 | 49 | 66   | 59 | 53 | 48 | 46   |
|        |           |                 |                 | 1.25          | 80   | 70  | 63 | 57  | 78   | 69  | 62 | 57  | 75   | 67 | 61 | 56 | 72   | 66 | 60 | 56 | 54   |
| 下方投影面積 |           | cm <sup>2</sup> | 1.5             | 84            | 75   | 68  | 63 | 82  | 74   | 68  | 63 | 79  | 72   | 67 | 62 | 76 | 70   | 66 | 61 | 59 |      |
| 等価発光面積 |           |                 | cm <sup>2</sup> | 2.0           | 90   | 82  | 76 | 72  | 88   | 81  | 76 | 71  | 85   | 79 | 74 | 70 | 82   | 77 | 73 | 70 | 67   |
| 取付高さ   | 器具間隔最大限   |                 | 2.5             | 93            | 87   | 82  | 77 | 92  | 86   | 81  | 77 | 89  | 84   | 80 | 76 | 86 | 82   | 78 | 75 | 73 |      |
|        | 横方向 ( A ) |                 | 縦方向 ( B )       | 3.0           | 96   | 90  | 86 | 82  | 94   | 89  | 85 | 81  | 91   | 87 | 83 | 80 | 89   | 85 | 82 | 79 | 76   |
| 1.5m   | 2.04 m    | 2.15 m          | 4.0             | 99            | 95   | 91  | 88 | 97  | 94   | 90  | 87 | 95  | 91   | 88 | 86 | 92 | 89   | 87 | 84 | 82 |      |
| 2      | 2.7       | 2.72            | 5.0             | 101           | 97   | 94  | 91 | 99  | 96   | 93  | 91 | 97  | 94   | 91 | 89 | 94 | 92   | 90 | 88 | 85 |      |
| 2.5    | 3.37      | 3.31            | 7.0             | 103           | 100  | 98  | 96 | 102 | 99   | 97  | 95 | 99  | 97   | 95 | 93 | 96 | 95   | 93 | 92 | 89 |      |
| 3      | 4.02      | 3.91            | 10.0            | 105           | 103  | 101 | 99 | 103 | 102  | 100 | 98 | 101 | 99   | 98 | 97 | 98 | 97   | 96 | 95 | 92 |      |

